

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Special Features

C8 #8 Cu Compression Splice

Nsi Industries	SSION Splice
Catalog Number	C8
Manufacturer	Nsi Industries
Description	Long Barrel TINNEDCOPPERSPLICE8 Awg Long Barrel Tinned Coppersplices Is A Type Of Copper Compression Connector That Is Produced From High Conductivity Copper Tubing. They Are Tin-Plated to Provide Corrosion Resistance and Are Marked With Die Index and Color Coded For Easy Reference. Listed For 35KV Maximum When Properly Installed.
Weight per unit	0.0400 (lbs/each)
Product Category	Splicing & Terminating Kits
Features	
Material	Copper
Number of Conductors	2
Poles	1
Voltage Rating	600 V
Warranty	
Material, Color, and Finish	
Color	Red
Finish	Tin Plated
Dimensions and Weight	
Size	L=1.75 - OD=.270 - ID=.170
Descriptions	
Description	#8 CU COMPRESSION SPLICE
extra long description	NSI C-8 CU CMP Splice Long 250 MCM
Features	Long Barrel TinnedCopperSplice8 AWG Long Barrel Tinned CopperSplices is a type of copper compression connector that is produced from high conductivity copper tubing. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.
Long Description	Long Barrel TinnedCopperSplice8 AWG Long Barrel Tinned CopperSplices is a type of copper compression connector that is produced from high conductivity copper tubing. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.
Product Type	Cu CMP Splice Long 250 MCM
0 115 1	"O ANAC (CTD) OLI C II

#8 AWG (STR) - CU Splice



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

N	lanut	facturer	Inform	nation
		4014.01		

Brand	NSi	
GTIN	00662381037497	
UPC	662381037497	

Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Туре	Long Barrel - CU Splice

Packaging

···~g···g	
Carton	1
Weight Per each	0.04

Uses, Certifications, and Standards

environmental conditions 90 C standard UL486A/B, UL467 (8 AWG -3/0 AWG) Temperature Pating 90 C	Application	Terminate, Splice, Tap Power Connectors
	environmental conditions	90 C
Tomporature Pating 90 C	standard	UL486A/B, UL467 (8 AWG -3/0 AWG)
remperature rating 70 G	Temperature Rating	90 C