

ELLIOTT ELECTRIC SUPPLY 425 East Germann Road Suite 101 85297-0000, AZ Gilbert Phone: 602-325-9757 Fax: 602-325-9758



CG1850S 1/2" STL STR Cord Appleton/Oz Gedney

Catalog Number	CG1850S
Manufacturer	Appleton/Oz Gedney
Description	Straight Liquidtight Strain Relief Connector, Size: 1/2 In, Conductor Range: 3/16 - 5/16 In, Material: Machined Steel, Color: Brown Label, Nema Rating: Nema 3R, Connection: Threaded Hub, Dimensions: 0.94 In Height, Standard: Class I, Div
Weight per unit	0.1400 (lbs/each)
Product Category	Cable & Cord Grips
eatures	
connection	Threaded Hub
Material, Color, and Finish	
Color	Brown
Dimensions and Weight	
Size	1/2
Descriptions	
Description	1/2" STL STR CORD
extra long description	APP CG-1850S 1/2 IN STL L-T CRD&CBL
Long Description	Straight Liquidtight Strain Relief Connector, Size: 1/2 IN, Conductor Range: 3/16 - 5/16 IN, Material: Machined Steel, Color: Brown Label, Nema Rating: NEMA 3R, Connection: Threaded Hub, Dimensions: 0.94 IN Height, Standard: Class I, Div
Product Type	1/2 In STL L-T CRD&CBL Conn
Special Features	Color coded identification label clearly states the catalog number and minimum-maximum cable diameter range for which the connector is designed; For use in wet or dry locations sealing electrical connections against dust and dirt, oil, water or other atmosphere containing moisture; Machined steel cap; Neoprene sealing grommet; Neoprene sealing grommet firmly but safely grips cable jacket providing strain relief while protecting interna wiring connections against external tension on cable or cord; Steel or Tefl
Manufacturer Information	
Brand	Appleton
GTIN	00781381449281
Manufacturers Part Number	CG-1850S
UPC	781381449281



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

425 East Germann Road Suite 101 85297-0000, AZ Gilbert Phone: 602-325-9757 Fax: 602-325-9758

Taxonomies, Classifications, and Ca	tegories
Category Description	CORD CONNECTORS & CORD GRIPS
Туре	Straight Liquidtight Strain Relief Connector
Packaging	
Carton	25
Weight Per each	0.14
Uses, Certifications, and Standards	
Application	For Flexible Type Neoprene, Hypalon And PVC Jacketed Power Or
	Control Cord And Cable
nema rating	3R
standard	Class I, Division 2, Class II, Division 1 And 2 Class III, UL 514B,

E14817, CSA C22.2 No. 18.3, 065178