



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



CH18B100C 18C 100A 1PH MB Loadcenter

Eaton Corp

Catalog Number	CH18B100C
Manufacturer	Eaton Corp
Description	CH 3/4-Inch Loadcenter, Main Breaker, 100A, C, Copper, CH8CF-Combination, CH8CS-Surface, Not Included, Nema 1, Metallic, 10 Kaic, CH, 18, 18, Three-Wire, Single-Phase, #6-1/0 Awg, Top/Bottom
Weight per unit	24.3 (lbs/each)
Product Category	Single Phase Main Breaker Load

Features

amperage rating	100
Cover Type	Ch8cf-combination, ch8cs-surface, not included
interrupt rating	10
max amps	100
max poles	18
media	Yes
number of spaces	18
Phase	1

Dimensions and Weight

Depth	21
Height	3.88
Size	C
Width	14.31

Descriptions

Description	18C 100A 1PH MB LOADCENTER
extra long description	ETN CH18B100C 1Ph/CH LC 100A 10KAIC
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for power distribution and circuit protection in residential and light commercial applications. Also called a breaker box, electrical box or even a fuse box, the main function is to take electricity supplied by the utility and distribute it throughout the home to feed lights and receptacles. Covers are typically packaged separately and available as surface or flush mount.
Long Description	CH 3/4-inch loadcenter, Main breaker, 100A, C, Copper, Ch8cf-combination, ch8cs-surface, not included, NEMA 1, Metallic, 10 kAIC, CH, 18, 18, Three-wire, Single-phase, #6-1/0 AWG, Top/bottom
Product Type	1PH/CH LC 100A 10KAIC MCB 18 Cir Cu, N1



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

Brand	EATON CUTLER-HAMMER
GTIN	00782113097565
Manufacturers Part Number	CH18B100C
UPC	782113097565

Taxonomies, Classifications, and Categories

Category Description	LOADCENTERS & COVERS
Type	Main breaker loadcenter

Availability

Status	Inactive
--------	----------

Packaging

Carton	1
Weight Per each	24.3

Uses, Certifications, and Standards

Application	Residential Bldgs & Facilities - Residential Bldgs & Facilities - OtherResidential Bldgs & Facilities - Residential Bldgs/Facilities - Aftermarket
standard	UL 50,UL 67