



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



CH220GF Type CH 5MA GFI Breaker 20A/2 Pole 120/240V 10K *Eaton Corp*

| | |
|------------------|---|
| Catalog Number | CH220GF |
| Manufacturer | Eaton Corp |
| Description | Type CH 3/4-Inch Ground Fault Circuit Breaker, Two-Pole, 20A, 120/240V, 10 Kaic, #14-6 Awg Cu/Al 60Å°C or 75Å°C |
| Weight per unit | 0.9000 (lbs/each) |
| Product Category | In Circuit Breakers |

Features

| | |
|------------------|----------|
| amperage rating | 20A |
| amps | 20 |
| interrupt rating | 10 |
| pole | Double |
| Poles | 2 |
| Trip Type | Common |
| Voltage Rating | 120/240V |

Dimensions and Weight

| | |
|--------|------|
| Height | 2 in |
| Length | 6 in |
| Width | 2 |

Descriptions

| | |
|------------------------|---|
| Description | TYPE CH 5MA GFI BREAKER 20A/2 POLE 120/240V 10K |
| extra long description | ETN CH220GF Type CH 3/4-inch Ground |
| Long Description | Type CH 3/4-inch Ground Fault Circuit Breaker, Two-Pole, 20A, 120/240V, 10 kAIC, #14-6 AWG Cu/Al 60Å°C or 75Å°C |
| Product Type | Type CH 3/4-Inch Ground Fault Circuit Breaker |
| Special Features | Ground fault |

Manufacturer Information

| | |
|---------------------------|---------------------|
| Brand | EATON CUTLER-HAMMER |
| GTIN | 00782113296159 |
| Manufacturers Part Number | CH220GF |
| UPC | 782113296159 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|------------------------------------|
| Category Description | Fault Sensing Breakers (AFCI/GFCI) |
|----------------------|------------------------------------|

Packaging

| | |
|-----------------|-----|
| Carton | 1 |
| Weight Per each | 0.9 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application
standard

Circuit Protection
UL 489