

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CH2L70SP 1 PH/CH Loadcntr 70A Mlo 2/4 Cir. Cu Bus Surface C Eaton Corp

Catalog Number	CH2L70SP
Manufacturer	Eaton Corp
Description	Eaton CH Main Lug Loadcenters, Standard, Main Lug Only, 70A, 5, Copper, Nema 1, Metallic, Top/Bottom, CH, Surface, 2, Four-Pole, 2, Three-Wire, Single-Phase, 120/240 V, #14-2 Awg
Weight per unit	3.7 (lbs/each)
Product Category	Single Phase Main Lug Load Cen
tures	
amperage rating	70
interrupt rating	25
media	Yes
number of spaces	2
Phase	1
Voltage Rating	120/240 V
Wattage	Four-pole Four-pole
nensions and Weight	
Depth	9.5
Height	3.13
Size	5
Width	4.5
scriptions	
Description	1 PH/CH LOADCNTR 70A MLO 2/4 CIR. CU BUS SURFACE C
extra long description	ETN CH2L70SP 1 Ph/CH LC 70A MLO 2/4
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for power distribution and circuit protection in residential and light commercial applications. Also called a breaker box, electrical box or even a fuse box, the main function is to take electricity supplied by the utility and distribute it throughout the home to feed lights and receptacles. Covers are typically packaged separately and available as surface or flush mount.
Long Description	Eaton CH main lug loadcenters, Standard, Main lug only, 70A, 5, Copper, NEMA 1, Metallic, Top/bottom, CH, Surface, 2, Four-pole, 2, Three-wire, Single-V, #14-2 AWG
Product Type	1 PH/CH LC 70A MIo 2/4 CKT Cu Bus Surf
Special Features	Standard



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

N	lanut	facturer	Inform	nation
		40.4.0.		

Brand	EATON CUTLER-HAMMER
GTIN	00782114190449
Manufacturers Part Number	CH2L70SP
UPC	782114190449

Taxonomies, Classifications, and Categories

Category Description	LOADCENTERS & COVERS
Туре	Main lug loadcenter

Packaging

onaging	
Carton	1
Weight Per each	3.7

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
Mounting	Surface Mount
standard	UL 50,UL 67