

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CH3080 Type CH BRKR 80A/3 Pole 240V 10K Eaton Corp

Catalog Number	CH3080
Manufacturer	Eaton Corp
Description	Eaton CH Thermal Magnetic Circuit Breaker, Type CH 3/4-Inch Standard Circuit Breaker, 80 A, 10 Kaic, Three-Pole, 240V, CH, Common Breaker Trip, #10-1/0 Awg Cu/AI, CH, Type CH Loadcenters
Weight per unit	0.8600 (lbs/each)
Product Category	19860110041921
atures	
amps	80
dimensions	3.5000 IN X 2.2500 IN X 3.5000 IN
interrupt rating	10 kAIC
pole #	Three
Poles	3
Тгір Туре	Common breaker trip
Voltage Rating	240 V - 240 V
scriptions	
Description	TYPE CH BRKR 80A/3 POLE 240V 10K
extra long description	ETN CH3080 Type CH Breaker 80A/3 Po
Features	Eaton's residential CH circuit breakers provide premium overloa
	protection. The Type CH circuit breakers trip to the OFF position
	eliminating nuisance callbacks. The CHF family also includes a tri
	flag to differentiate between a trip and the breaker being turned
	off. The thermal-magnetic trip curve avoids nuisance tripping or mild overloads while reacting almost instantaneously to severe
	short-circuit conditions. Multiple breakers have an internal
	common trip connection to operate all poles simultaneous
Long Description	Eaton CH thermal magnetic circuit breaker, Type CH 3/4-Inch
	standard circuit breaker,80 A,10
	kAIC,Three-pole,240V,CH,Common breaker trip,#10-1/0 AWG
	Cu/AI,CH,Type CH Loadcenters
Product Type	Type CH Breaker 80A/3 Pole 240V 10K
anufacturer Information	
Brand	EATON CUTLER-HAMMER
GTIN	00782113146768
Manufacturers Part Number	CH3080
UPC	782113146768



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	Loadcenter Plug In Breakers and Accessories
Туре	Thermal magnetic circuit breakers
Packaging	
Carton	
Weight Per each	0.86
Uses, Certifications, and Standards	
Application	Datacenters - IT Space: CI and Hyper ConvergedMarine Vessels and Equipment - Marine Vessels and Equipment - OtherOtherGeneration - Renewable Energy - Alternative EnergyGeneration - Conventional Energy - Conventional Energy
standard	UL 489