

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CHMS Blank Dead Front Directory Marking Strip *Eaton Corp*

3001	
Catalog Number	CHMS
Manufacturer	Eaton Corp
Description	Eaton CH 3/4-Inch Loadcenter and Breaker Accessories - Circuit Marking Strip, Circuit Marking Strip, CH, 0.75 In, Used With Type CH Style 3/4 In Loadcenter and Breakers
Weight per unit	0.1000 (lbs/each)
Product Category	Load Center Accessories
eatures	
amperage rating	225
dimensions	4.0000 IN X 7.0000 IN X 0.0100 IN
interrupt rating	10
media	Yes
Phase	3
mensions and Weight	
Depth	4
Height	0.01
Width	7
escriptions	
Description	BLANK DEAD FRONT DIRECTORY MARKING STRIP
extra long description	ETN CHMS Blank Dead Front Directory
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for power distribution and circuit protection in residential and light commercial applications. Also called a breaker box, electrical box or even a fuse box, the main function is to take electricity supplied by the utility and distribute it throughout the home to feed lights and receptacles. Covers are typically packaged separately and available as surface or flush mount.
Long Description	Eaton CH 3/4-inch Loadcenter and Breaker Accessories - Circuit Marking Strip, Circuit marking strip, CH, 0.75 in, Used with Type CH Style 3/4 in Loadcenter and Breakers
Product Type	Blank Dead Front Directory Marking Strip
Special Features	Used with Type CH Style 3/4 in Loadcenter and Breakers
anufacturer Information	• • • • • • • • • • • • • • • • • • •
Brand	EATON CUTLER-HAMMER
GTIN	00782113099729
Manufacturers Part Number	CHMS
UPC	782113099729



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and	Categories	
Туре	Accessory	
Packaging		
Carton	1	
Package	10	
Weight Per each	0.1	
Uses, Certifications, and Standa	ds	
Application	Other	
standard	UL 489	