



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## CHN250SUR Surge Breaker, 2P, 50A, 120/240V, 10kaic *Eaton Corp*

Catalog Number	CHN250SUR
Manufacturer	Eaton Corp
Description	Eaton CH Residential Surge Breaker, 2P, 50A, 120/240V, 10KAIC, Pigtail Neutral
Weight per unit	0.6000 (lbs/each)
Product Category	2 Pole

### Features

amperage rating	30 A
dimensions	3.5000 IN X 3.5000 IN X 2.2300 IN

### Descriptions

Description	SURGE BREAKER, 2P, 50A, 120/240V, 10KAIC
extra long description	ETN CHN250SUR Surge Breaker, 2P, 50
Features	Eaton offers a comprehensive family of surge products for use at service entrances. These products can help protect sensitive electronics against the damaging effects of surges. Due to the evolution of electronics and microprocessors in the home, there is a continuous challenge to provide quality (clean) power for electronic loads such as appliances, computers/home office and entertainment systems. Surges caused by lightning, utility grid switching and other sources travel on current carrying conductors t
Long Description	Eaton CH residential surge breaker, 2P, 50A, 120/240V, 10KAIC, PIGTAIL NEUTRAL
Product Type	Surge Breaker, 2P, 50A, 120/240V, 10kaic

### Manufacturer Information

Brand	Eaton
GTIN	00786689217198
Manufacturers Part Number	CHN250SUR
UPC	786689217198

### Taxonomies, Classifications, and Categories

Type	Surge breaker
------	---------------

### Packaging

Carton	1
Weight Per each	0.6



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Uses, Certifications, and Standards

Application

Generation - Conventional Energy - Conventional  
EnergyOtherDatacenters - IT Space: CI and Hyper  
ConvergedMarine Vessels and Equipment - Marine Vessels and  
Equipment - OtherGeneration - Renewable Energy - Alternative  
Energy

standard

UL 1449,UL 489