



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



CLNSURGE Eaton Type CL Circuit Bre

Eaton Corp

Catalog Number	CLNSURGE
Manufacturer	Eaton Corp
Description	Eaton Type CL Circuit Breaker Surge Protective Device, Plug On Surge Protective Device UI Classified
Weight per unit	1.0 (lbs/each)
Product Category	Line Construction Material

Features

dimensions	3.0710 IN X 1.9800 IN X 2.9810 IN
------------	-----------------------------------

Dimensions and Weight

Depth	3.0710
Height	2.9810
Width	1.9800

Descriptions

Description	EATON TYPE CL CIRCUIT BRE
extra long description	EWD CLNSURGE Plug on Surge Arrester
Features	Eaton offers a comprehensive family of surge products for use at service entrances. These products can help protect sensitive electronics against the damaging effects of surges. Due to the evolution of electronics and microprocessors in the home, there is a continuous challenge to provide quality (clean) power for electronic loads such as appliances, computers/home office and entertainment systems. Surges caused by lightning, utility grid switching and other sources travel on current carrying conductors t
Long Description	Eaton Type CL circuit breaker surge protective device, Plug On Surge Protective Device UL Classified
Product Type	Plug On Surge Arrester UI Classified

Manufacturer Information

Brand	Eaton
GTIN	00786689353698
Manufacturers Part Number	CLNSURGE
UPC	786689353698

Taxonomies, Classifications, and Categories

Type	Plug on module surge protection device
------	----------------------------------------

Packaging

Carton	1
Weight Per each	1



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Other Residential Bldgs & Facilities - Residential Bldgs & Facilities - Other
Frequency Rating	50/60 Hz
standard	UL 1449,cUL Certified