


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





CPR7 2-1/2" Rigid Connector Threadless *Crouse-Hinds*

Catalog Number	CPR7
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series CPR Compression Connector,
	Rigid/Imc, Straight, Non-Insulated, Malleable Iron, 2-1/2"
Weight per unit	3.1 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

dimensions 2.9400 IN X 3.7500 IN X 3.7500 IN Material Malleable Iron

Dimensions and Weight

2-1/2 in Size

Descriptions

Construction	Concrete Tight
Description	2-1/2" RIGID CONNECTOR THREADLESS
extra long description	MIDWEST CPR7 2 1/2 RGD CMP CONN
Features	Crouse-Hinds series rigid/IMC connectors, couplings and combination couplings are used to join used to join rigid/IMC conduit to a box or enclosure, or to couple two ends of conduit together. Our rigid/IMC connectors and couplings are available in set screw type and compression type, in both insulated and non-insulated versions. They are available in a variety of materials to suit customer preferences, including malleable iron, steel, zinc die cast, aluminum, stainless steel and hot dip galvanized mallea
Long Description	Eaton Crouse-Hinds series CPR compression connector, Rigid/IMC, Straight, Non-insulated, Malleable iron, 2-1/2"
Product Type	2 1/2 RGD CMP Conn

Manufacturer Information

Brand	Eaton
GTIN	00784564122070
Manufacturers Part Number	CPR7
UPC	784564122070

Taxonomies, Classifications, and Categories

Category Description	Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS
	AND THREADLESS CONNECTOR
Туре	Compression Connector



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	2
Weight Per each	3.05
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 514B, CUL