



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## CS68 4 to 4 Alcu Comp Splice

*Abb Installation Products, Inc*

Catalog Number	CS68
Manufacturer	Abb Installation Products, Inc
Description	Service Entrance Compression Splice, #4 Awg (Ascr);#2 Awg (Solid ) Conductor Size, Non-Insulated, Copper/Aluminum Conductor Material, 2 In Overall Length, Compression/Crimp Terminal, 0.08 LB/Ea
Weight per unit	0.0570 (lbs/each)
Product Category	Large Terminals & Connectors

### Features

connection	Compression
insulation	None
Material	Aluminum
Number of Conductors	2

### Dimensions and Weight

Size	2 INCH
------	--------

### Descriptions

Description	4 TO 4 ALCU COMP SPLICE
extra long description	ABB CS68 AL SERVENTR COMP SPLICE A:

### Manufacturer Information

Brand	Blackburn Mechanical
GTIN	00783786100989
UPC	783786100989

### Taxonomies, Classifications, and Categories

Category Description	SPLIT BOLTS
Type	Compression Splice Service Entrance

### Packaging

Carton	100
Package	800
Weight Per each	0.057



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Uses, Certifications, and Standards

Application	Basic, uninsulated Splices for Service Entrances. For Combinations of Aluminum-to-Aluminum or Aluminum-to-Copper Conductors
environmental conditions	All Seasons / Conditions
Mounting standard	None
	RUS Accepted. Complies with ANSI C119.4 when properly installed on Aluminum-to-Aluminum or Aluminum-to-Copper Conductors