

Cable Standoffs



CS4



CS4 Holds...

- One 14/3 to one 10/3
- Three 14/2 W/G to three 10/3 CS7 Holds...
- Up to five runs of 12/2 non-metallic sheathed cable.
- Up to eight runs of Cat 5 cable.
- Up to four runs of Cat 6 cable.
- Up to five runs of coaxial cable.


Positions non-metallic sheathed cable, phone/data cable, and coaxial cable. Installs with a screw or nail. Nail included with CS4.

FEATURES AND BENEFITS

- Positions cables at a safe distance from nailing surface
- CS4 provides a neat, organized cable installation and prevents tangles
- CS7 positions cable 2" from a furring strip or 2x4 stud
- CS7 features positive lock to keep cables in place
- Positions both flat and round NM cables
- Complies with 2014 NEC Article 300.4d

| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | UNIT PKG | STD PKG | DIM A | DIM B | DIM C |
|-------------------|-----------------------------|-------------|------------|----------|----------|----------|
| CS4 | 50174 | 100 | 100 | 4.100 | .750 | 1.200 |
| CS7* | 71007 | 100 | 100 | 3.490 | .880 | .740 |

*UL and CSA only. Note: For position only.







Cable Standoffs



CS4



CS4 Holds...

- One 14/3 to one 10/3
- Three 14/2 W/G to three 10/3 CS7 Holds...
- Up to five runs of 12/2 non-metallic sheathed cable.
- Up to eight runs of Cat 5 cable.
- Up to four runs of Cat 6 cable.
- Up to five runs of coaxial cable.

Positions non-metallic sheathed cable, phone/data cable, and coaxial cable. Installs with a screw or nail. Nail included with CS4.

FEATURES AND BENEFITS

- Positions cables at a safe distance from nailing surface
- CS4 provides a neat, organized cable installation and prevents tangles
- CS7 positions cable 2" from a furring strip or 2x4 stud
- CS7 features positive lock to keep cables in place
- Positions both flat and round NM cables
- Complies with 2014 NEC Article 300.4d

| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | UNIT PKG | STD PKG | DIM A | DIM B | DIM C |
|-------------------|-----------------------------|-------------|------------|----------|----------|----------|
| CS4 | 50174 | 100 | 100 | 4.100 | .750 | 1.200 |
| CS7* | 71007 | 100 | 100 | 3.490 | .880 | .740 |

*UL and CSA only. Note: For position only.

