

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CT106 3-4 Main Copper C Tap

Nsi Industries	opper o rap		
Catalog Number	CT106		
Manufacturer	Nsi Industries		
Description	Copper C Tap Grounding Connector For 3 to 4 Awg Copper "C" Taps Ensure Positive, All Around Compression With		
	Low-Resistance and High Pull-Out Values. Made Of High Conductivity Copper, They Satisfy The Requirements Of NEC250-81 and 250-91 For Connecting to The Grounding		
	Electrode System. Rated 600 Volts.		
Weight per unit	0.0400 (lbs/each)		
Product Category	Large Terminals & Connectors		
Features			
Conductor Size	4 AWG		
Material	Copper		
Tap Size	4 AWG		
Voltage Rating	600 V		
Warranty	1 YEAR		
Material, Color, and Finish			
Color	Pink		
Finish	COPPER		
Dimensions and Weight			
Size	4-4 AWG		
Descriptions			
Description	3-4 MAIN COPPER C TAP		
extra long description	NSI CT-106 Copper C Tap 3-4 Main		
Features	Copper C Tap Grounding Connector for 3 to 4 AWG Copper "C"		
1 0010/100	Taps ensure positive, all around compression with low-resistance		
	and high pull-out values. Made of high conductivity copper, they		
	satisfy the requirements of NEC250-81 and 250-91 for connecting		
	to the grounding electrode system. Rated 600 Volts.		
Long Description	Copper C Tap Grounding Connector for 3 to 4 AWG Copper "C"		
	Taps ensure positive, all around compression with low-resistance		
	and high pull-out values. Made of high conductivity copper, they		
	satisfy the requirements of NEC250-81 and 250-91 for connecting		
	to the grounding electrode system. Rated 600 Volts.		
Product Type	Copper C Tap 3-4 Main		
Special Features	4-4 AWG		



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

N	lanuf	actur	er In	forma	tion
---	-------	-------	-------	-------	------

Brand	NSi
GTIN	00662381098054
Manufacturers Part Number	CT-106
UPC	662381098054

Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Type	C-Taps

Packaging

,,,ag.,,g		
Carton	1	
Package		
Weight Per each	0.04	

Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors	
environmental conditions	90 C	
standard	UL486	
Temperature Rating	90 C	