

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



D2RR4T1 Ice Cube Relay 4PDT 6A 24VDC Coil Eaton Corp

| Catalog Number | D2RR4T1 |
|------------------------------------|---|
| Manufacturer | Eaton Corp |
| Description | Ice Cube Relay, 4PDT, 6A, 24VDC Coil_ |
| Weight per unit | 0.1000 (lbs/each) |
| Product Category | In Relays & Accessories |
| Features | |
| amperage rating | 10A |
| Contact Rating | 10 A |
| dimensions | 1.3800 IN X 1.2000 IN X 1.4000 IN |
| Number of Pins | 11 |
| Poles | Four-pole |
| Descriptions | |
| Description | ICE CUBE RELAY 4PDT 6A 24VDC COIL |
| extra long description | ETN D2RR4T1 ICE CUBE RELAY, 4PDT, 6 |
| Features | Installation of general purpose relays are quick, easy and secure |
| | with little risk of damage, and various relay models are |
| | specifically slim-form designed to fit into tight spaces. |
| | The D series ice cube general purpose relays provide excellent |
| | functionality and are ideal for any application from controlling |
| | smaller loads, to those requiring high current-carrying capacity. A |
| | wide array of coil voltages and contact configurations ensure |
| | there is a D series relay for every control circuit design |
| | application. |
| Long Description | ICE CUBE RELAY, 4PDT, 6A, 24VDC COIL_ |
| Product Type | Ice Cube Relay, 4PDT, 6A, 24VDC Coil |
| Manufacturer Information | |
| Brand | Eaton |
| GTIN | 00786685929941 |
| Manufacturers Part Number | D2RR4T1 |
| UPC | 786685929941 |
| Taxonomies, Classifications, and C | Categories |
| Category Description | GENERAL PURPOSE RELAYS |
| Туре | General-purpose relay |
| Packaging | |
| Carton | 1 |
| Weight Per each | 0.1 |



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

| Application | Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other |
|-----------------------|--|
| Operating Temperature | -30° to 50°C |
| standard | UL Listed, CE Marked, RoHS Compliant |