

Eaton D3PR5A

Catalog Number: D3PR5A

D3 Series General Purpose Plug-In Relay, Latching cover, 11 pins, 120V coil, 10,000 Ohms resistance, Octal terminal, DPDT contact configuration, 16A contact rating, Silver alloy contacts, IP40 enclosure



General specifications

| | |
|-----------------------------|-----------------------------|
| Product Name | Catalog Number |
| Eaton General-purpose relay | D3PR5A |
| UPC | Product Length/Depth |
| 782114227732 | 2 in |
| Product Height | Product Width |
| 2 in | 1 in |
| Product Weight | Compliances |
| 0.5 lb | CE Marked |
| | RoHS Compliant |
| Certifications | |
| CSA Certified | |
| UL Listed | |
| cRUus | |

Product specifications

Type

General-purpose relay

Cover

Latching

Options

Plain cover relay

Coil voltage

120 V

Contact configuration

DPDT

Contact material

Silver alloy

Contact rating

16 A

Enclosure

IP40

Number of pins

11

Resistance

10,000 Ω

Series

D3

Terminals

Octal

Voltage - max

300 V switching

Resources

Specifications and datasheets

[Eaton Specification Sheet - D3PR5A](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)

Eaton D3PR5A

Catalog Number: D3PR5A

D3 Series General Purpose Plug-In Relay, Latching cover, 11 pins, 120V coil, 10,000 Ohms resistance, Octal terminal, DPDT contact configuration, 16A contact rating, Silver alloy contacts, IP40 enclosure



General specifications

| | |
|-----------------------------|-----------------------------|
| Product Name | Catalog Number |
| Eaton General-purpose relay | D3PR5A |
| UPC | Product Length/Depth |
| 782114227732 | 2 in |
| Product Height | Product Width |
| 2 in | 1 in |
| Product Weight | Compliances |
| 0.5 lb | CE Marked |
| | RoHS Compliant |
| Certifications | |
| CSA Certified | |
| UL Listed | |
| cRUus | |

Product specifications

Type

General-purpose relay

Cover

Latching

Options

Plain cover relay

Coil voltage

120 V

Contact configuration

DPDT

Contact material

Silver alloy

Contact rating

16 A

Enclosure

IP40

Number of pins

11

Resistance

10,000 Ω

Series

D3

Terminals

Octal

Voltage - max

300 V switching

Resources

Specifications and datasheets

[Eaton Specification Sheet - D3PR5A](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)