(1)

Strain Relief Grips - Deluxe Cord Grips

Deluxe cord grips are woven of stainless steel mesh with an aluminum body for corrosion resistance. They are offered in single/double weave construction to help absorb direct pull, to resist flexing and binding, and to eliminate strain. They are recommended for indoor or outdoor use where subjected to moisture in the wiring of pendant stations, processing equipment, hand tools, and extension cord sets. Deluxe grips are suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2.



Deluxe Cord Grips Straight Male Connector

3/8" NPT Deluxe Cord Grips

Cord Diameter	Straight Male Catalog No.	90° Male Catalog No.	9
0.19-0.25" (4.8-6.4mm)	□ DC000187 •	□ DC000187-90	•
0.25-0.31" (6.4-7.9mm)	□ DC000250 •	□ DC000250-90	•
0.31-0.38" (7.9-9.7mm)	□ DC000312 •	□ DC000312-90	•
0.38-0.50" (9.7-12.7mm)	□ DC000375 •	□ DC000375-90	•



Deluxe Cord Grips 90° Male Connector

1/2" NPT Deluxe Cord Grips

Cord Diameter Straight Male Catalog No. 90° Male Catalog No. 45° Male Catalog No. Straight Female Catalog No. 0.19-0.25" (4.8-6.4mm) □ DC100187 • □ DC100187-90 • □ DC100187-45 • □ DC100187-F 0.25-0.38" (6.4-9.6mm) □ DC100250 • □ DC100250-90 • □ DC100250-45 • □ DC100250-F 0.38-0.50" (9.7-12.7mm) □ DC100375 • □ DC100375-90 • □ DC100375-45 • □ DC100375-F 0.50-0.63" (12.7-16.0mm) □ DC100500 • □ DC100500-90 • □ DC100500-45 • □ DC100500-F 0.63-0.75" (16.0-19.1mm) □ DC100625 • □ □ - □ - 0.75-0.88" (19.1-22.4mm) □ DC100750 • □ - □ -					•
0.25-0.38" (6.4-9.6mm) DC100250 DC100250-90 DC100250-45 DC100250-F 0.38-0.50" (9.7-12.7mm) DC100375 DC100375-90 DC100375-45 DC100375-F 0.50-0.63" (12.7-16.0mm) DC100500 DC100500-90 DC100500-45 DC100500-F 0.63-0.75" (16.0-19.1mm) DC100625 - - -	Cord Diameter	Straight Male Catalog No.	90° Male Catalog No.		Straight Female Catalog No.
0.38-0.50" (9.7-12.7mm) DC100375 DC100375-90 DC100375-45 DC100375-F 0.50-0.63" (12.7-16.0mm) DC100500 DC100500-90 DC100500-45 DC100500-F 0.63-0.75" (16.0-19.1mm) DC100625 — — —	0.19-0.25" (4.8-6.4mm)	□ DC100187 •	□ DC100187-90	• □ DC100187-45 •	□ DC100187-F •
0.50-0.63" (12.7-16.0mm)	0.25-0.38" (6.4-9.6mm)	□ DC100250 •	□ DC100250-90	• □ DC100250-45 •	□ DC100250-F •
0.63-0.75" (16.0-19.1mm) DC100625 • — — — —	0.38-0.50" (9.7-12.7mm)	□ DC100375 •	□ DC100375-90	• □ DC100375-45 •	□ DC100375-F •
, , ,	0.50-0.63" (12.7-16.0mm)	□ DC100500 •	□ DC100500-90	• □ DC100500-45 •	□ DC100500-F •
0.75-0.88" (19.1-22.4mm) □ DC100750 • — — — —	0.63-0.75" (16.0-19.1mm)	□ DC100625 •	_	_	_
	0.75-0.88" (19.1-22.4mm)	□ DC100750 •	_	_	



Deluxe Cord Grips 45° Male Connector

3/4" NPT Deluxe Cord Grips

3/4" NPT Deluxe Cord Grips				
Cord Diameter	Straight Male Catalog No.	90° Male Catalog No.	45° Male Catalog No.	Straight Female Catalog No.
0.25-0.38" (6.4-9.6mm)	□ DC200250 •	□ DC200250-90 •	□ DC100250-45 •	□ DC200250-F •
0.38-0.50" (9.7-12.7mm)	□ DC200375 •	□ DC200375-90 •	□ DC100375-45 •	□ DC200375-F •
0.50-0.63" (12.7-16.0mm)	□ DC200500 •	□ DC200500-90 •	□ DC100500-45 •	□ DC200500-F •
0.63-0.75" (16.0-19.1mm)	□ DC200625 •	□ DC200625-90 •	□ DC200625-45 •	□ DC200625-F •
0.75-0.88" (19.1-22.4mm)	□ DC200750 •	_	_	_



Deluxe Cord Grips
Straight Female Connector

Icon Key



