

Description

The E4RTATSB is a remodel Non-IC Air-Tite™ housing optimized and listed for EISA compliant tungsten-halogen lamps, CFL and LED lamps as well as incandescent. Housing features an adjustable socket bracket, and is suitable for residential or commercial applications. Installation in non-insulated ceilings with Air-Tite code compliant construction. If insulation is present it must be kept 3" from all sides of the housing. May be retrofit with compatible Halo LED lighting systems.

| | | |
|-------------|--|------|
| Catalog # | | Type |
| Project | | |
| Comments | | Date |
| Prepared by | | |

Specification Features

Housing

- Die-formed CRS
- For installation from below the finished ceiling
- Air-Tite gasket pre-installed on remodel flange

Remodel Clips

- Four remodel clips secure housing and accommodates 1/2" and 5/8" ceiling materials.

Junction Box

- Seven conduit knockouts are uniform 1/2" size with true pry-out slots
- Four pry-outs with integral strain relief simplify "NM" non-metallic sheathed cable installation
- Three quick connect wire connectors included

Includes:

Quick Connect™

- (3) Push wire nuts included, for speed & reliability
- Clear caps for wire connection visibility

Air-Tite™ code compliant

- ASTM E283 compliant

Socket

- Adjustable position porcelain socket with nickel plated brass screw shell provides flexibility in lamp positioning.

Thermal Protector

- Self resetting thermal protector deactivates fixture if overheating occurs due to improper lamping or misapplied insulation.

Trims

- Halo Fit-All concept offers multiple trim options in a variety of design styles, and functional beam distributions to control beam angle and lumen delivery in accommodating various lamp types

Compliance

- cULus Listed 1598 Luminaire
- cULus Listed for Damp Location
- cULus Listed for Wet Location, with select trims
- RoHS compliant
- Air-Tite code compliant. Certified under ASTM E283; not exceeding 2.0 cfm (0.944 L/s) air leakage rate tested at a 1.57 psf (75 Pa) pressure differential



E4RTATSB

4" Non-Insulated Ceiling AIR-TITE Remodel Housing with Adjustable Socket Bracket


4" Trims



FOR USE IN EXISTING CEILINGS

FOR USE IN NON-INSULATED CEILINGS OR INSULATED CEILINGS BUT INSULATION MUST BE KEPT 3" FROM ALL SIDES OF FIXTURE

Dimensions



Ordering Information

Sample Number: E4RTATSB 4003SC
 Order housing, trim and lamp (by others) separately for a complete luminaire.

Housing

E4RTATSB = 4" non-insulated ceiling AIR-TITE small aperture remodel housing with adjustable socket bracket

Trims

Reflectors



999 Reflector Cone
 OD: 5-1/16" [129mm]
999P=Specular Clear, White Trim Ring
999RG=Residential Gold, White Trim Ring
999W=White Reflector, White Trim Ring
999H=Haze Reflector, White Trim Ring
999MB=Specular Black Reflector, White Trim Ring
999SN=Satin Nickel Reflector with Satin Nickel Trim Ring
999TBZ=Tuscan Bronze Reflector with Tuscan Bronze Trim Ring



4003 Reflector Cone
 OD: 4-3/4" [120mm]
4003SC=Specular Clear Reflector, White Trim Ring

Baffles



953 Metal Baffle
 OD: 5-1/16" [129mm]
953P=Black Baffle with White Trim Ring
953W=White Baffle with White Trim Ring
953SN=Satin Nickel Baffle with Satin Nickel Trim Ring
953TBZ=Tuscan Bronze Baffle with Tuscan Bronze Trim Ring



990 Pinhole Trim
 OD: 5-1/16" [129mm]
990P=White Die Cast Trim
990AC=Antique Copper Die Cast Trim
990SN=Satin Nickel Die Cast Trim
990TBZ=Tuscan Bronze Die Cast Trim

Baffles



992 Wall Wash with Baffle
 OD: 5-1/16" [129mm]
992P=White Scoop and Trim Ring, Black Baffle
992AC=Antique Copper, Scoop and Trim Ring, Black Baffle
992W=White Scoop and Trim Ring, White Baffle
993SN=Satin Nickel Scoop and Trim Ring, Black Baffle
993TBZ=Tuscan Bronze Scoop and Trim Ring, Black Baffle



993 Coil Baffle
 OD: 5-1/16" [129mm]
993P=Black Baffle with White Trim Ring
993W=White Baffle with White Trim Ring
993SN=Black Baffle with Satin Nickel Trim Ring
993TBZ=Black baffle with Tuscan Bronze Trim Ring



4001 Step Baffle
 OD: 4-3/4" [120mm]
4001BB=Black Plastic Baffle, White Trim Ring
4001WB=White Plastic Baffle, White Trim Ring



4010 Metal Baffle
 OD: 5" [127mm]
4010BB=Black Metal Baffle, White Trim Ring
4010WB=White Metal Baffle, White Trim Ring



4013 Metal Baffle
 OD: 5" [127mm]
4013BB=Black Metal Baffle, White Trim Ring
4013WB=White Metal Baffle, White Trim Ring

Adjustable



996 Eyeball 15° Tilt
 OD: 5-1/16" [129mm]
996P=White Eyeball
996SN=Satin Nickel Eyeball
996TBZ=Tuscan Bronze Eyeball



998 Eyeball 30° Tilt
 OD: 5-1/16" [129mm]
998P=White Eyeball
998SN=Satin Nickel Eyeball
998TBZ=Tuscan Bronze Eyeball



4002 Eyeball
 OD: 4-3/4" [120mm]
4002WH=White Eyeball

Lens / Wet Location Listed



951 Prismatic Glass Lens with Full Cone Reflector
951PS=Full Reflector and Glass Lens, White Trim
951SNS=Full Reflector and Glass Lens, Satin Nickel Trim
951TBZS=Full Reflector and Glass Lens, Tuscan Bronze Trim



952 Cone Reflector
952PS=White Trim Ring, Dome Lens Shower Light



945 Metropolitan Ice Light
 OD: 5-5/16" [135mm]
945=Clear Frosted
945Blue=Blue Frosted



4055 Prismatic Glass Lens Shower Light
 OD: 4-3/4" [120mm]
4055WH=Shower Light, White Trim Ring, Prismatic Flat Glass Lens



For use in Halo listed housings.

Description

The E4RTATSB is a remodel Non-IC Air-Tite™ housing optimized and listed for EISA compliant tungsten-halogen lamps, CFL and LED lamps as well as incandescent. Housing features an adjustable socket bracket, and is suitable for residential or commercial applications. Installation in non-insulated ceilings with Air-Tite code compliant construction. If insulation is present it must be kept 3" from all sides of the housing. May be retrofit with compatible Halo LED lighting systems.

| | | |
|-------------|--|------|
| Catalog # | | Type |
| Project | | |
| Comments | | Date |
| Prepared by | | |

Specification Features

Housing

- Die-formed CRS
- For installation from below the finished ceiling
- Air-Tite gasket pre-installed on remodel flange

Remodel Clips

- Four remodel clips secure housing and accommodates 1/2" and 5/8" ceiling materials.

Junction Box

- Seven conduit knockouts are uniform 1/2" size with true pry-out slots
- Four pry-outs with integral strain relief simplify "NM" non-metallic sheathed cable installation
- Three quick connect wire connectors included

Includes:

Quick Connect™

- (3) Push wire nuts included, for speed & reliability
- Clear caps for wire connection visibility

Air-Tite™ code compliant

- ASTM E283 compliant

Socket

- Adjustable position porcelain socket with nickel plated brass screw shell provides flexibility in lamp positioning.

Thermal Protector

- Self resetting thermal protector deactivates fixture if overheating occurs due to improper lamping or misapplied insulation.

Trims

- Halo Fit-All concept offers multiple trim options in a variety of design styles, and functional beam distributions to control beam angle and lumen delivery in accommodating various lamp types

Compliance

- cULus Listed 1598 Luminaire
- cULus Listed for Damp Location
- cULus Listed for Wet Location, with select trims
- RoHS compliant
- Air-Tite code compliant. Certified under ASTM E283; not exceeding 2.0 cfm (0.944 L/s) air leakage rate tested at a 1.57 psf (75 Pa) pressure differential



E4RTATSB

**4" Non-Insulated Ceiling
AIR-TITE Remodel Housing
with Adjustable Socket
Bracket**



4" Trims



**FOR USE IN EXISTING
CEILINGS**

**FOR USE IN
NON-INSULATED CEILINGS
OR
INSULATED CEILINGS BUT
INSULATION MUST BE
KEPT 3" FROM ALL SIDES
OF FIXTURE**

Dimensions



Ordering Information

Sample Number: E4RTATSB 4003SC
 Order housing, trim and lamp (by others) separately for a complete luminaire.

Housing

E4RTATSB = 4" non-insulated ceiling AIR-TITE small aperture remodel housing with adjustable socket bracket

Trims

Reflectors



999 Reflector Cone
 OD: 5-1/16" [129mm]
999P=Specular Clear, White Trim Ring
999RG=Residential Gold, White Trim Ring
999W=White Reflector, White Trim Ring
999H=Haze Reflector, White Trim Ring
999MB=Specular Black Reflector, White Trim Ring
999SN=Satin Nickel Reflector with Satin Nickel Trim Ring
999TBZ=Tuscan Bronze Reflector with Tuscan Bronze Trim Ring



4003 Reflector Cone
 OD: 4-3/4" [120mm]
4003SC=Specular Clear Reflector, White Trim Ring

Baffles



953 Metal Baffle
 OD: 5-1/16" [129mm]
953P=Black Baffle with White Trim Ring
953W=White Baffle with White Trim Ring
953SN=Satin Nickel Baffle with Satin Nickel Trim Ring
953TBZ=Tuscan Bronze Baffle with Tuscan Bronze Trim Ring



990 Pinhole Trim
 OD: 5-1/16" [129mm]
990P=White Die Cast Trim
990AC=Antique Copper Die Cast Trim
990SN=Satin Nickel Die Cast Trim
990TBZ=Tuscan Bronze Die Cast Trim

Baffles



992 Wall Wash with Baffle
 OD: 5-1/16" [129mm]
992P=White Scoop and Trim Ring, Black Baffle
992AC=Antique Copper, Scoop and Trim Ring, Black Baffle
992W=White Scoop and Trim Ring, White Baffle
993SN=Satin Nickel Scoop and Trim Ring, Black Baffle
993TBZ=Tuscan Bronze Scoop and Trim Ring, Black Baffle



993 Coil Baffle
 OD: 5-1/16" [129mm]
993P=Black Baffle with White Trim Ring
993W=White Baffle with White Trim Ring
993SN=Black Baffle with Satin Nickel Trim Ring
993TBZ=Black baffle with Tuscan Bronze Trim Ring



4001 Step Baffle
 OD: 4-3/4" [120mm]
4001BB=Black Plastic Baffle, White Trim Ring
4001WB=White Plastic Baffle, White Trim Ring



4010 Metal Baffle
 OD: 5" [127mm]
4010BB=Black Metal Baffle, White Trim Ring
4010WB=White Metal Baffle, White Trim Ring



4013 Metal Baffle
 OD: 5" [127mm]
4013BB=Black Metal Baffle, White Trim Ring
4013WB=White Metal Baffle, White Trim Ring

Adjustable



996 Eyeball 15° Tilt
 OD: 5-1/16" [129mm]
996P=White Eyeball
996SN=Satin Nickel Eyeball
996TBZ=Tuscan Bronze Eyeball



998 Eyeball 30° Tilt
 OD: 5-1/16" [129mm]
998P=White Eyeball
998SN=Satin Nickel Eyeball
998TBZ=Tuscan Bronze Eyeball



4002 Eyeball
 OD: 4-3/4" [120mm]
4002WH=White Eyeball

Lens / Wet Location Listed



951 Prismatic Glass Lens with Full Cone Reflector
951PS=Full Reflector and Glass Lens, White Trim
951SNS=Full Reflector and Glass Lens, Satin Nickel Trim
951TBZS=Full Reflector and Glass Lens, Tuscan Bronze Trim



952 Cone Reflector
952PS=White Trim Ring, Dome Lens Shower Light



945 Metropolitan Ice Light
 OD: 5-5/16" [135mm]
945=Clear Frosted
945Blue=Blue Frosted



4055 Prismatic Glass Lens Shower Light
 OD: 4-3/4" [120mm]
4055WH=Shower Light, White Trim Ring, Prismatic Flat Glass Lens



For use in Halo listed housings.