

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

E57LAL12A2 12MM STD Ind Prox 2W Ac

Catalog Number	E57LAL12A2
Manufacturer	Eaton Corp
Description	Eaton Premium+ Inductive Proximity Sensor, E57, 2 MM Range, Straight, 12 MM, Shielded, 360° Viewable Led, 6.6 FT, 250 Ma At 250V, <3% Sensing Range, PVC, 2-Wire Ac, No, 20-250V
Weight per unit	0.7000 (lbs/each)
Product Category	Inductive Proximity Sensor
Features	
Accuracy	< 3% sensing range
dimensions	2.4600 IN X 0.4700 IN X 0.4700 IN
media	Yes
thread size/sense distance	12mm/2mm
Descriptions	
Description	12MM STD IND PROX 2W AC
extra long description	ETN E57LAL12A2 12MM STD IND PROX 2W
Features	E57G general purpose sensors are a cost-effective solution that is optimised to include only those functions that are necessary for basic, reliable sensing without lacking the performance or features you expect in an Eaton product. These sensors include various diameter options designed to fit a variety of applications.
Long Description	Eaton Premium+ Inductive Proximity Sensor, E57, 2 mm range, Straight, 12 mm, Shielded, 360° viewable LED, 6.6 ft, 250 mA at 250V, <3% sensing range, PVC, 2-wire AC, NO, 20-250V
Product Type	12MM STD Ind Prox 2W Ac
Manufacturer Information	
Brand	EATON CUTLER-HAMMER
GTIN	00782113742946
Manufacturers Part Number	E57LAL12A2
UPC	782113742946
Taxonomies, Classifications, and C	ategories
Category Description	CENCODO
Туре	Inductive Proximity Sensor
Packaging	
	1
Manufacturers Part Number UPC Taxonomies, Classifications, and C Category Description	E57LAL12A2 782113742946 Fategories SENSORS

0.7



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Stationary Mach Equip In Factory - Other Stationary Machinery and Equipment - In Factory
environmental conditions	NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13, IP67, IP69K
standard	CSA Certified,UL Listed,CE Marked