






Complete Cables

| Accessory | Description | For Use With . . . | Catalog Number | Price | Discount Code |
|---|--|--------------------|-----------------|-------|---------------|
| Programming Cables | | | | | |
|  | SUB-D 9-pole, serial, 2m (6.5 ft) | EASY500 EASY700 | EASY-PC-CAB | 201 | E20 |
| | | EASY800 MFD-CP8 | EASY800-PC-CAB | 215 | E20 |
| | USB, 2m (6.5 ft) | EASY500 EASY700 | EASY-USB-CAB | 325 | E20 |
| | | EASY800 MFD-CP8 | EASY800-USB-CAB | 325 | E20 |
| Point-to-point Connection Cable | | | | | |
|  | Serial interface for connecting EASY800 to MFD- . . . CP8 Can be configured as required with separate plug Length: 5 m (16.4 ft), can be cut as needed | EASY800 MFD-CP8 | MFD-800-CAB5 | 270 | E20 |
| Network Cables | | | | | |
|  | Cable length: 0.3 m (0.98 ft) | easy-NET | EASY-NT-30 | 26 | E20 |
| | Cable length: 0.8 m (2.62 ft) | | EASY-NT-80 | 44 | E20 |
| | Cable length: 1.5 m (4.92 ft) | | EASY-NT-150 | 68 | E20 |
| PROFIBUS-DP Bus Connector Plug | | | | | |
|  | 9-pin connector Cable entry Angled 90° | PROFIBUS-DP | ZB4-209-DS2 | 225 | E23 |
| | Metallic insulated housing Maximum transfer rate: 12 Mbit/s Integrated switch for bus terminating resistors Terminal block for two cable entries with straight or angled 90°, as needed | EASY204-DP | ZB4-209-DS3 | 225 | E22 |





Turn to
next page
for more
cabling
options



Display Adapter

| Accessory | Description | For Use With... | Catalog Number | Price | Discount Code |
|---|---|-------------------------------------|----------------|-------|---------------|
| Display Adapter | | | | | |
|  | Connection of EASY800 to MI4 operator panel, in conjunction with EASY800-PC-CAB | EASY800 / MFD-CP8 EASY800-PC-CAB | ZB4-03B-AD1 | 150 | E22 |


Complete Cables

| Accessory | Description | For Use With . . . | Catalog Number | Price | Discount Code |
|---|--|--------------------|-----------------|-------|---------------|
| Programming Cables | | | | | |
|  | SUB-D 9-pole, serial, 2m (6.5 ft) | EASY500 EASY700 | EASY-PC-CAB | 201 | E20 |
| | | EASY800 MFD-CP8 | EASY800-PC-CAB | 215 | E20 |
| | USB, 2m (6.5 ft) | EASY500 EASY700 | EASY-USB-CAB | 325 | E20 |
| | | EASY800 MFD-CP8 | EASY800-USB-CAB | 325 | E20 |
| Point-to-point Connection Cable | | | | | |
|  | Serial interface for connecting EASY800 to MFD- . . . CP8 Can be configured as required with separate plug Length: 5 m (16.4 ft), can be cut as needed | EASY800 MFD-CP8 | MFD-800-CAB5 | 270 | E20 |
| Network Cables | | | | | |
|  | Cable length: 0.3 m (0.98 ft) | easy-NET | EASY-NT-30 | 26 | E20 |
| | Cable length: 0.8 m (2.62 ft) | | EASY-NT-80 | 44 | E20 |
| | Cable length: 1.5 m (4.92 ft) | | EASY-NT-150 | 68 | E20 |
| PROFIBUS-DP Bus Connector Plug | | | | | |
|  | 9-pin connector Cable entry Angled 90° | PROFIBUS-DP | ZB4-209-DS2 | 225 | E23 |
| | Metallic insulated housing Maximum transfer rate: 12 Mbit/s Integrated switch for bus terminating resistors Terminal block for two cable entries with straight or angled 90°, as needed | EASY204-DP | ZB4-209-DS3 | 225 | E22 |

Turn to
next page
for more
cabling
options



Display Adapter

| Accessory | Description | For Use With... | Catalog Number | Price | Discount Code |
|---|---|-------------------------------------|----------------|-------|---------------|
| Display Adapter | | | | | |
|  | Connection of EASY800 to MI4 operator panel, in conjunction with EASY800-PC-CAB | EASY800 / MFD-CP8 EASY800-PC-CAB | ZB4-03B-AD1 | 150 | E22 |