

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Category Description

Type

ED3200 Ed 65KA @ 240 V 3 Pole 200AS Load Terms Eaton Corp

Catalog Number	ED3200
Manufacturer	Eaton Corp
Description	Eaton Series C Complete Molded Case Circuit Breaker, F-Frame, Ed, Complete Breaker, Fixed Thermal, Fixed Magnetic Trip Type Three-Pole, 200 A, 240 Vac, 125 VDC, 65 Kaic At 240 Vac, 50/60 HZ
Weight per unit	4.5 (lbs/each)
Product Category	3 Pole
eatures	
Current Rating	200 A
dimensions	3.3800 IN X 4.1300 IN X 6.0000 IN
media	Yes
Poles	Three-pole
Тгір Туре	Fixed thermal, fixed magnetic
Voltage Rating	240 Vac, 125 Vdc
escriptions	
Description	ED 65KA @ 240 V 3 POLE 200AS LOAD TERMS
extra long description	ETN ED3200 ED 65kA @240 V, 3P 200 A
Features	Experience the superior quality of the Eaton Series C Molded Case Circuit Breaker. The Series C circuit breaker is ideal for panelboards, switchboards, motor control centers, and busway applications. Choose from a premier selection of trip units including thermal magnetic, electronic, and magnetic only switches. Available for systems up to 600 VAC or 250 VDC with current ratings up to 800A.
Long Description	Eaton Series C complete molded case circuit breaker, F-frame, ED, Complete breaker, Fixed thermal, Fixed magnetic trip type, Three-pole, 200 A, 240 Vac, 125 Vdc, 65 kAIC at 240 Vac, 50/60 Hz
Product Type	Ed / EVA @240 V/ 2D 200 As Load Torreinal
lanufacturer Information	
Brand	Eaton
GTIN	00786679455142
Manufacturers Part Number	ED3200
UPC	786679455142

MOLDED CASE BREAKERS

Molded case circuit breaker



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	4.45
Uses, Certifications, and Standards	
Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies, Panels and EOEMs
Frequency Rating	50 to 60 Hz
standard	UL Listed