



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## EYD46 1-1/4" Fem/Male Drain

*Crouse-Hinds*

Catalog Number	EYD46
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eyd Conduit Sealing Fitting With Drain, Male and Female, Feraloy Iron Alloy and/or Ductile Iron, Vertical Only, 1-1/4"
Weight per unit	2.8 (lbs/each)
Product Category	Sealing Bodies

### Features

connection	Female Threaded, Female Threaded
dimensions	2.1900 IN X 2.1900 IN X 5.0600 IN

### Material, Color, and Finish

Finish	Untreated
--------	-----------

### Descriptions

Description	1-1/4" FEM/MALE DRAIN
extra long description	CRS-H EYD46 1 1/4 EYD DRAIN SEAL MA
Features	In addition to restricting the passage of gases, vapors or flames from one portion of the electrical installation to another, Crouse-Hinds series EYD and EZD drain sealing fittings prevent accumulation of condensate above the seal. They are installed in vertical conduit runs and at low points in conduit systems.
Long Description	Eaton Crouse-Hinds series EYD conduit sealing fitting with drain, Male and female, Feraloy iron alloy and/or ductile iron, Vertical only, 1-1/4"
Product Type	1 1/4 Eyd Drain Seal Male-Female Hub
Special Features	With Drain, Vertical Position

### Manufacturer Information

Brand	Eaton
GTIN	00782274376301
Manufacturers Part Number	EYD46
UPC	782274376301

### Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Type	Conduit sealing fitting with drain

### Packaging

Carton	1
Package	2
Weight Per each	2.75



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure standard	Class I Div 1 2 Group C D, Class II Div 1 2 Group F G, Class III UL 886, CSA C22.2