

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



EYS014 6" Female Cond Seal

Crouse-Hinds

Catalog Number	EYS014
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eys Conduit Sealing Fitting, Female,
	Feraloy Iron Alloy and/or Ductile Iron, Vertical or Horizontal, 6"
Weight per unit	39.3 (lbs/each)
Product Category	Sealing Bodies

Features

connection	Female Threaded, Female Threaded
dimensions	13.2500 IN X 12.0000 IN X 9.7500 IN

Material, Color, and Finish

|--|

Descriptions

Description	6" FEMALE COND SEAL
extra long description	CRS-H EYS014 6 NPT FEM CST IRON VER
Features	Crouse-Hinds series EYS and EZS explosionproof sealing fittings restrict the passage of gases, vapors or flames from one portion of the electrical installation to another, limit explosions to the sealed off enclosure, and limit pre-compression or "pressure piling" in conduit systems. EYS sealing fittings are available for installation in either vertical only or in both horizontal or vertical positions. They are available in a variety of materials, including Feraloy iron alloy and/or ductile iron, copper-
Long Description	Eaton Crouse-Hinds series EYS conduit sealing fitting, Female, Feraloy iron alloy and/or ductile iron, Vertical or horizontal, 6"
Product Type	6 NPT Fem CST Iron Vert/Horz Seal FTG
Special Features	Vertical/Horizontal

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274377100
Manufacturers Part Number	EYS014
UPC	782274377100

Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Туре	Conduit sealing fitting
ackaning	

Packaging

Carton	1
Weight Per each	39.2999

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	CLASS I DIV 1 2 GROUP C D, CLASS II DIV 1 2 GROUP E F G, CLASS
	III
standard	UL 886, CSA C22.2