

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

EYS4 1-1/4" Male & Female Hub Vertical Seal Off *Crouse-Hinds*

Catalog Number	EYS4
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eys Conduit Sealing Fitting, Female, Feraloy Iron Alloy and/or Ductile Iron, Vertical or Horizontal, 1-1/4"
Weight per unit	2.6 (lbs/each)
Product Category	Sealing Bodies
eatures	
connection	Female Threaded, Female Threaded
dimensions	5.0000 IN X 2.0000 IN X 3.0000 IN
Material, Color, and Finish	
Finish	Untreated
escriptions	
Description	1-1/4" MALE & FEMALE HUB VERTICAL SEAL OFF
extra long description	CRS-H EYS4 1 1/4 NPT FEM CST IRON V
Features	Crouse-Hinds series EYS and EZS explosionproof sealing fittings restrict the passage of gases, vapors or flames from one portior of the electrical installation to another, limit explosions to the sealed off enclosure, and limit pre-compression or "pressure piling" in conduit systems. EYS sealing fittings are available for installation in either vertical only or in both horizontal or vertical positions. They are available in a variety of materials, including Feraloy iron alloy and/or ductile iron, copper-
Long Description	Eaton Crouse-Hinds series EYS conduit sealing fitting, Female, Feraloy iron alloy and/or ductile iron, Vertical or horizontal, 1-1/4"
Product Type	1 1/4 NPT Fem CST Iron Vert/Horz Seal FT
Special Features	
Nanufacturer Information	
Brand	Eaton
GTIN	00782274377704
	EYS4
Manufacturers Part Number	L137

Conduit sealing fitting



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

a				

Carton	2	
Package	20	
Weight Per each	2.58	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	CLASS I DIV 1 2 GROUP C D, CLASS II DIV 1 2 GROUP E F G, CLASS
	III
standard	UL 886, CSA C22.2