

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



EYS416 1-1/4" Male & Female Hub Vert/Horizontal Seal Off Crouse-Hinds

Catalog Number	EYS416				
Manufacturer	Crouse-Hinds				
Description	Eaton Crouse-Hinds Series Eys Conduit Sealing Fitting, Male and Female, Feraloy Iron Alloy and/or Ductile Iron, Vertical or Horizontal, Group B Rated, 1-1/4"				
Weight per unit	3.0 (lbs/each)				
Product Category	Sealing Bodies				
eatures					
connection	Male Threaded, Female Threaded				
dimensions	2.1900 IN X 2.1900 IN X 5.0600 IN				
Material, Color, and Finish					
Finish	Electrogalvanized With Aluminum Acrylic Painted				
escriptions	· ·				
Description	1-1/4" MALE & FEMALE HUB VERT/HORIZONTAL SEAL OFF				
extra long description	CRS-H EYS416 1 1/4 NPT MALE/FEM IRO				
Features	Crouse-Hinds series EYS and EZS explosionproof sealing fittings restrict the passage of gases, vapors or flames from one portion of the electrical installation to another, limit explosions to the sealed off enclosure, and limit pre-compression or "pressure piling" in conduit systems. EYS sealing fittings are available for installation in either vertical only or in both horizontal or vertical positions. They are available in a variety of materials, including Feraloy iron alloy and/or ductile iron, copper-				
Long Description	Eaton Crouse-Hinds series EYS conduit sealing fitting, Male and female, Feraloy iron alloy and/or ductile iron, Vertical or horizontal, Group B rated, 1-1/4"				
Product Type	1 1/4 NPT Male/Fem Iron Ver/Hor Seal FT				
Special Features	Horizontal/Vertical Position				
lanufacturer Information					
Brand	Eaton				
GTIN	00782274276984				
Manufacturers Part Number	EYS416				
UPC	782274276984				
axonomies, Classifications, and	Categories				
	HAZARDOUS LOCATION FITTINGS				
-					

Conduit sealing fitting



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

P	a	C	K	a	g	I	n	g

Carton	1	
Package	2	
Weight Per each	2.95	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group B C D, Class Ii Div 1 2 Group E F G, Class Iii
standard	UL 886, CSA C22.2