

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

EYS96 3-1/2" Female/Male Cond Seal Crouse-Hinds

Catalog Number	EYS96
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eys Conduit Sealing Fitting, Male and Female, Feraloy Iron Alloy and/or Ductile Iron, Vertical or Horizontal, 3-1/2"
Weight per unit	16.0 (lbs/each)
Product Category	Sealing Bodies
atures	
connection	Female Threaded, Female Threaded
dimensions	4.7500 IN X 4.7500 IN X 9.1900 IN
aterial, Color, and Finish	
Finish	Untreated
escriptions	
Description	3-1/2" FEMALE/MALE COND SEAL
extra long description	CRS-H EYS96 IRON SEALING FTG
Features	Crouse-Hinds series EYS and EZS explosionproof sealing fittings restrict the passage of gases, vapors or flames from one portion of the electrical installation to another, limit explosions to the sealed off enclosure, and limit pre-compression or "pressure piling" in conduit systems. EYS sealing fittings are available for installation in either vertical only or in both horizontal or vertical positions. They are available in a variety of materials, including Feraloy iron alloy and/or ductile iron, copper-
Long Description	Eaton Crouse-Hinds series EYS conduit sealing fitting, Male and female, Feraloy iron alloy and/or ductile iron, Vertical or horizontal, 3-1/2"
Product Type	Iron Sealing FTG
Special Features	Vertical/Herizontal
anufacturer Information	
Brand	Eaton
GTIN	00782274379906
Manufacturers Part Number	EYS96
UPC	782274379906

Category Description HAZARDOUS LOCATION FITTINGS

Conduit sealing fitting



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Pac	kag	ıng
	<u> </u>	

Carton	1	
Weight Per each	15.95	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	CLASS I DIV 1 2 GROUP C D, CLASS II DIV 1 2 GROUP E F G, CLASS
	[I]
standard	UL 886, CSA C22.2