



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## EYSX11 1/2" Female Cond Seal

*Crouse-Hinds*

Catalog Number	EYSX11
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eysx Expanded Fill Sealing Fitting, Female, Feraloy Iron Alloy, Vertical or Horizontal, Group B Rated, 1/2"
Weight per unit	1.3 (lbs/each)
Product Category	Sealing Bodies

### Features

connection	Female Threaded, Female Threaded
dimensions	1.5000 IN X 1.5000 IN X 3.6900 IN

### Material, Color, and Finish

Finish	Electrogalvanized With Aluminum Acrylic Painted
--------	---

### Descriptions

Description	1/2" FEMALE COND SEAL
extra long description	CRS-H EYSX11 1/2 FEM VERT/HORZ EXPA
Features	EYSX expanded fill sealing fittings from Eaton Crouse-Hinds Division provide 40% wire fill capacity to allow uninterrupted runs in a conduit system. They are designed to restrict the passage of gases, vapors or flames from one portion of the electrical installation to another, limit explosions to the sealed off enclosure, and limit pre-compression or "pressure piling" in conduit systems. EYSX expanded fill sealing fittings are available for installation in both horizontal or vertical positions.
Long Description	Eaton Crouse-Hinds series EYSX expanded fill sealing fitting, Female, Feraloy iron alloy, Vertical or horizontal, Group B rated, 1/2"
Product Type	1/2 Fem Vert/Horz Expand Fill Sealing FT
Special Features	Horizontal/Vertical Position

### Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274943169
Manufacturers Part Number	EYSX11
UPC	782274943169

### Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Type	Expanded fill sealing fitting



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

Carton	1
Weight Per each	1.26

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure standard	Class I Div 1 2 Group B C D, Class II Div 1 2 Group E F G, Class III
	UL 886, CSA C22.2