

**Product Number:** 21513

**Order Abbreviation:** F15T12/CW/6PK

**General Description:** 15W T12 preheat fluorescent lamp, Cool White phosphor, 4200K color temperature, 60 CRI, 6 pack



**\* Full Case Required**

#### Product Information

|                              |                        |
|------------------------------|------------------------|
| Abbrev. With Packaging Info. | F15T12CW6PK 6/CS 1/SKU |
| Actual Length (in)           | 17.780                 |
| Actual Length (mm)           | 451.61                 |
| Average Rated Life (hr)      | 9000                   |
| Base                         | Medium Bipin           |
| Bulb                         | T12                    |
| Color Rendering Index (CRI)  | 60                     |
| Color Temperature/CCT (K)    | 4200                   |
| Diameter (in)                | 1.591                  |
| Diameter (mm)                | 40.40                  |
| Industry Standards           | ANSI C78.81 - 2001     |
| Initial Lumens at 25C        | 750                    |
| Mean Lumens at 25C           | 653                    |
| Nominal Length (in)          | 18.000                 |
| Nominal Length (mm)          | 457.20                 |
| Nominal Wattage (W)          | 15.00                  |

#### Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.

**Product Number:** 21513

**Order Abbreviation:** F15T12/CW/6PK

**General Description:** 15W T12 preheat fluorescent lamp, Cool White phosphor, 4200K color temperature, 60 CRI, 6 pack



**\* Full Case Required**

#### Product Information

|                              |                        |
|------------------------------|------------------------|
| Abbrev. With Packaging Info. | F15T12CW6PK 6/CS 1/SKU |
| Actual Length (in)           | 17.780                 |
| Actual Length (mm)           | 451.61                 |
| Average Rated Life (hr)      | 9000                   |
| Base                         | Medium Bipin           |
| Bulb                         | T12                    |
| Color Rendering Index (CRI)  | 60                     |
| Color Temperature/CCT (K)    | 4200                   |
| Diameter (in)                | 1.591                  |
| Diameter (mm)                | 40.40                  |
| Industry Standards           | ANSI C78.81 - 2001     |
| Initial Lumens at 25C        | 750                    |
| Mean Lumens at 25C           | 653                    |
| Nominal Length (in)          | 18.000                 |
| Nominal Length (mm)          | 457.20                 |
| Nominal Wattage (W)          | 15.00                  |

#### Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.