

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Product Type

F2X1LG6 2X1X72" LT Gry NM Slot Duct Panduit Corporation

Catalog Number	F2X1LG6
Manufacturer	Panduit Corporation
Description	The F2X1LG6 Panduct Lead-Free PVC Narrow Slot Wiring Duct Features A Narrow Slot/Finger Design That Closely Matches The Spacing Of High-Density Components. Upper and Lower Scorelines Allow For Easy Finger/Sidewall Section Removal. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use
	Temperature Up to 122°F (50°C). Mounting Holes Provided. Lead-Free PVC. 2" X 1" (50.8 MM X 25.4 MM) and 6' (1.83 M) Long. Cover Sold Separately. Color Light Gray.
Weight per unit	0.1533 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray
eatures	
connection	Mounting Holes
Material	PVC
media	Yes
Material, Color, and Finish	
Color	Gray
Dimensions and Weight	
Height	1.12
Length	NA
Size	2.00 x 1.00
Width	2,25
Descriptions	
Description	2X1X72" LT GRY NM SLOT DUCT
extra long description	PAN F2X1LG6 Panduct® F2X1LG6 Base W
Long Description	The F2X1LG6 Panduct Lead-Free PVC Narrow Slot Wiring Duct features a narrow slot/finger design that closely matches the spacing of high-density components. Upper and lower scoreline allow for easy finger/sidewall section removal. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. Lead-free PVC. 2" x 1" (50.8 mm x 25.4 mm) and 6' (1.83 m) long. Cover sold

separately. Color Light Gray.

Panduct® F2X1LG6 Base Wiring Duct



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

$N/I \cap P$	ヘレリナヘヘナ	IIPAP IMI	formation

Brand	PANDUIT
GTIN	00074983375455
Manufacturers Part Number	F2X1LG6
UPC	074983375455

Taxonomies, Classifications, and Categories

Category Description	WIRE DUCT AND COVERS
Туре	Base Wiring Duct

Availability

minimum qty 6

Packaging

magnig		
Carton	6	
Package	120	
Weight Per foot	0.1533	

Uses, Certifications, and Standards

Application	Narrow slot/finger design provides more slots to fit the spacing
	of high-density terminal block applications
standard	RoHS Compliant, UL Recognized, CE Compliant