



GE
Lighting

66342 - F32T8/SPX65/ECO2

F32 T8 6500K Product Line Extension



GENERAL CHARACTERISTICS

| | |
|-----------------------------------|--------------------------------------|
| Lamp Type | Linear Fluorescent - Straight Linear |
| Bulb | T8 |
| Base | Medium Bi-Pin (G13) |
| Rated Life (NOM) | 30000.0 h |
| Rated Life (instant start) @ Time | 21000 h @ 3 h |
| Rated Life (rapid start) @ Time | 30000 h @ 12 h |
| | 30000.0 @ 3.0/36000.0 @ 12.0 h |
| Bulb Material | Sodalime glass |
| Starting Temperature (MIN) | 10.0 °C |
| Mercury Content (NOM) | 2.95 mg |
| Picograms of Mercury (NOM) | 35.69268 pg |
| Primary Application | Full Wattage |

PHOTOMETRIC CHARACTERISTICS

| | |
|---------------------------------------|----------|
| Initial Lumens (NOM) | 2900.0 |
| Mean Lumens (NOM) | 2755.0 |
| Nominal Initial Lumens per Watt (NOM) | 90.625 |
| Color Temperature (NOM) | 6500.0 K |
| Color Rendering Index (CRI) (NOM) | 78.0 |

ELECTRICAL CHARACTERISTICS

| | |
|---------------|------|
| Wattage (NOM) | 32.0 |
|---------------|------|

DIMENSIONS

| | |
|------------------------------------|----------------------|
| Maximum Overall Length (MOL) (NOM) | 48.000 in(1219.2 mm) |
| Nominal Length (NOM) | 48.000 in(1219.2 mm) |
| Bulb Diameter (DIA) (NOM) | 1.000 in(25.4 mm) |

PRODUCT INFORMATION

| | |
|----------------------------|------------------|
| Product Code | 66342 |
| Description | F32T8/SPX65/ECO2 |
| Standard Package | Case |
| Standard Package GTIN | 10043168663424 |
| Standard Package Quantity | 36 |
| Sales Unit | Unit |
| No Of Items Per Sales Unit | 1 |
| UPC | 043168663427 |



GE
Lighting

66342 - F32T8/SPX65/ECO2

F32 T8 6500K Product Line Extension



GENERAL CHARACTERISTICS

| | |
|-----------------------------------|--------------------------------------|
| Lamp Type | Linear Fluorescent - Straight Linear |
| Bulb | T8 |
| Base | Medium Bi-Pin (G13) |
| Rated Life (NOM) | 30000.0 h |
| Rated Life (instant start) @ Time | 21000 h @ 3 h |
| Rated Life (rapid start) @ Time | 30000 h @ 12 h |
| | 30000.0 @ 3.0/36000.0 @ 12.0 h |
| Bulb Material | Sodalime glass |
| Starting Temperature (MIN) | 10.0 °C |
| Mercury Content (NOM) | 2.95 mg |
| Picograms of Mercury (NOM) | 35.69268 pg |
| Primary Application | Full Wattage |

PHOTOMETRIC CHARACTERISTICS

| | |
|---------------------------------------|----------|
| Initial Lumens (NOM) | 2900.0 |
| Mean Lumens (NOM) | 2755.0 |
| Nominal Initial Lumens per Watt (NOM) | 90.625 |
| Color Temperature (NOM) | 6500.0 K |
| Color Rendering Index (CRI) (NOM) | 78.0 |

ELECTRICAL CHARACTERISTICS

| | |
|---------------|------|
| Wattage (NOM) | 32.0 |
|---------------|------|

DIMENSIONS

| | |
|------------------------------------|----------------------|
| Maximum Overall Length (MOL) (NOM) | 48.000 in(1219.2 mm) |
| Nominal Length (NOM) | 48.000 in(1219.2 mm) |
| Bulb Diameter (DIA) (NOM) | 1.000 in(25.4 mm) |

PRODUCT INFORMATION

| | |
|----------------------------|------------------|
| Product Code | 66342 |
| Description | F32T8/SPX65/ECO2 |
| Standard Package | Case |
| Standard Package GTIN | 10043168663424 |
| Standard Package Quantity | 36 |
| Sales Unit | Unit |
| No Of Items Per Sales Unit | 1 |
| UPC | 043168663427 |