

# ELLIOTT ELECTRIC SUPPLY 520 Equity Ave 72032-0000, AR Conway Phone: 501-336-8444 Fax: 501-329-5636



#### FD3 1G Dev Box Crouse-Hinds

Catalog Number	FD3
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet FD Device Box, Deep, Feraloy Iron Alloy, Single-Gang, 1"
Weight per unit	2.4 (11 ( 1.)
Product Category	FS & FD Type Boxes & Covers

#### **Features**

Cable Entry	(1) End
dimensions	5.2800 IN X 2.6900 IN X 2.7500 IN
Material	Electrogalvanized With Aluminum Acrylic Painted Feraloy Iron
	Alloy

## **Dimensions and Weight**

C170	- 1	 n	ı
Size	- 1		

### **Descriptions**

Description	1G DEV BOX
extra long description	CRS-H FD3 1 NPT DE IRON FD BX SGL G
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hub configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Long Description	Eaton Crouse-Hinds series Condulet FD device box, Deep, Feraloy iron alloy, Single-gang, 1"
Product Type	1 NPT De Iron FD BX SGL GNG MTG Lugs
Special Features	Configuration Type FD, Dimension 2-3/4 In Width X 2-11/16 In Depth X 5-9/32 In Height

#### **Manufacturer Information**

Brand	Eaton
GTIN	00782274397009
UPC	782274397009

#### **Taxonomies, Classifications, and Categories**

Category Description	FS BOXES AND COVERS
Type	DEVICE BOX



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

520 Equity Ave 72032-0000, AR Conway Phone: 501-336-8444

Fax: 501-329-5636

<sup>2</sup> ackaging		
Carton	1	
Package	2	
Weight Per each	1 18	

### Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	FLUSH
standard	UL 514, CSA C22.2, Federal Specification W-C-5860