

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



**UPC** 

### FDC222 2G Dev Box Crouse-Hinds

Crouse-Hinds	
Catalog Number	FDC222
Manufacturer	Crouse Hinds
Description	Eaton Crouse-Hinds Series Condulet FD Device Box, Deep, Feraloy Iron Alloy, Two-Gang, C Shape, 3/4"
Weight per unit	4.4 (lbs/each)
Product Category	FS & FD Type Boxes & Covers
Features	
Cable Entry	(1) Each End
dimensions	4.1900 IN X 2.6900 IN X 5.9400 IN
Material	Electrogalvanized With Aluminum Acrylic Painted Feraloy Iron Alloy
Dimensions and Weight	
Size	3/4 in
Descriptions	
Description	2G DEV BOX
extra long description	CRS-H FDC222 3/4 NPT CST IRON FD BX
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hub configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Long Description	Eaton Crouse-Hinds series Condulet FD device box, Deep, Feraloy iron alloy, Two-gang, C shape, 3/4"
Product Type	3/4 NPT CST Iron FD BX Two GNG MTG Lugs
Special Features	Configuration Type FDC, With Mounting Lug, Dimension 4-5/8 In Width X 2-11/16 In Depth X 6-1/16 In Height
Manufacturer Information	
Brand	Eaton
GTIN	00782274398600
Manufacturers Part Number	FDC222

782274398600



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

<b>Taxonomies, Classifications, and Categories</b>
--

Category Description	FS BOXES AND COVERS
Туре	DEVICE BOX

#### Packaging

ckaging	
Carton	1
Weight Per each	4.35

#### Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	SURFACE
standard	UL 514, CSA C22.2, Federal Specification W-C-5860