

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

FMVA13LWYUNV176 93W 100-277V 3000K Yk MT Led Flood Crouse-Hinds

Catalog Number	FMVA13LWYUNV176
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Champ Fmva Led Floodlight, Warm White, Dimmable Driver, 3/4" Entry, 400W Equiv, Heat and Impact Resistant Glass Lens, 13000 Lumens, 143 LM/W, Die Cast Aluminum, Yoke Mount, 100-277 Vac, 108-250 VDC, 95W, 7X6 Optics
Weight per unit	32.5 (lbs/each)
Product Category	20190822163614
Features	
dimensions	15.5000 IN X 7.0000 IN X 12.0000 IN
Descriptions	
Description	93W 100-277V 3000K YK MT LED FLOOD
extra long description	CRS-H FMVA13LWY-UNV1-76 LED FLOOD W
Features	Crouse-Hinds series Champ FMVA LED floodlights are designed to provide full-spectrum, crisp, white light in Class I and Class II hazardous areas. Eleven versions of the Champ FMVA are available, ranging from 3,000 to 50,000 lumens, providing a reliable and long-life solution for a wide range of floodlighting applications. Champ FMVA LED floodlights are certified for use in NEC, CEC and IEC hazardous locations, providing a single solution for applications around the world. These floodlights are ideal for
Long Description	Eaton Crouse-Hinds series Champ FMVA LED floodlight, Warm white, Dimmable driver, 3/4" entry, 400W equiv, Heat and impact resistant glass lens, 13000 lumens, 143 lm/W, Die cast aluminum, Yoke mount, 100-277 Vac, 108-250 Vdc, 95W, 7x6 optics
Product Type	Led Flood Warm Glass Lens 100-277 Vac 108-250 VDC
Manufacturer Information	
Brand	Eaton
GTIN	00662276879546
Manufacturers Part Number	FMVA13LWY-UNV1-76
UPC	662276879546
Taxonomies, Classifications, and (
Category Description	LED FLOODLIGHTS, WALLPACKS, BOLLARDS & LANDSCAPE

LIGHTING FLOODLIGHT



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	32.5
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Lighting and Lighting Controls