


# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





### FNQR.5 1/2A 600V TD Class CC Fuse

Bussmann Fuses

Catalog Number	FNOR.5
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series FNQ-R Fuse, 0.5 A, Class CC,
	Non-Indicating, Ferrule End X Ferrule End, 12 Sec At 200%, 200
	Kaic, Melamine Tube, Standard, 600 V
Weight per unit	0.0200 (lbs/each)
Product Category	Small Dimension Fuses

#### **Features**

amperage rating	0.5 A
class	Class CC
connection	Ferrule End X Ferrule End
dimensions	1.5000 IN X 0.4100 IN X 0.4100 IN
interrupt rating	200 kAIC
Material	Melamine Tube
media	Yes
Response Time	12 S at 200%
Voltage Rating	600 V

# **Dimensions and Weight**

13/32 In Diameter X 1-1/2 In Length Size

#### **Descriptions**

Description	1/2A 600V TD CLASS CC FUSE
extra long description	BUSS FNQ-R-1/2 CLASS CC TIME DELAY
Features	Bussmann's Class CC fuses set the standard in Class CC fuse performance in the industry. Recognized for their superior performance, Bussmann has the right product for your circuit and equipment protection needs. These branch circuit rated, 600v, 200,000a IR fuses offer exceptional protection in the smallest package of any UL class of fuses. Choose from the ultimate protection provided by our Low Peak LP-CC fuses, the time delay of our FNQ-R's for your control transformer and similar control applications or
Long Description	Eaton Bussmann series FNQ-R fuse, 0.5 A, Class CC, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 200 kAIC, Melamine tube, Standard, 600 V
Product Type	Class CC Time Delay
Special Features	Rejection Style



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

n	/lanufac	HILPAR	INTARMA	TION

Brand	Eaton
GTIN	00051712147019
Manufacturers Part Number	FNQ-R-1/2
UPC	051712147019

### **Taxonomies, Classifications, and Categories**

Category Description	MIDGET FUSES
Type	FUSE

#### **Packaging**

onaging		
Carton	10	
Weight Per each	0.02	

# Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	RoHS Compliant,CE Marked