


ELLIOTT ELECTRIC SUPPLY 3130 S Dodge Boulevard 85713-0000, AZ Tucson Phone: 520-526-1947 Fax: 520-526-1948



Bussmann Fuses

Catalog Number	FNQR4
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series FNQ-R Fuse, 4 A, Class CC, Non-Indicating, Ferrule End X Ferrule End, 12 Sec At 200%, 200 Kaic, Melamine Tube, Standard, 600 V
Weight per unit	0.0200 (lbs/each)
Product Category	Small Dimension Fuses

Features

amperage rating	4 A
class	Class CC
connection	Ferrule End X Ferrule End
dimensions	0.4100 IN X 0.4100 IN X 1.5000 IN
interrupt rating	200 kAIC
Material	Melamine Tube
media	Yes
Voltage Rating	600 V

Descriptions

Description	4A 600V TD CLASS CC FUSE
extra long description	EFSE FNQ-R-4 CLASS CC TIME DELAY
Features	Bussmann's Class CC fuses set the standard in Class CC fuse performance in the industry. Recognized for their superior performance, Bussmann has the right product for your circuit and equipment protection needs. These branch circuit rated, 600v, 200,000a IR fuses offer exceptional protection in the smallest package of any UL class of fuses. Choose from the ultimate protection provided by our Low Peak LP-CC fuses, the time delay of our FNQ-R's for your control transformer and similar control applications or
Long Description	Eaton Bussmann series FNQ-R fuse, 4 A, Class CC, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 200 kAIC, Melamine tube, Standard, 600 V
Product Type	Class CC Time Delay
Special Features	Rejection Style

Manufacturer Information

Brand	Eaton
GTIN	00051712147095
Manufacturers Part Number	FNO-R-4
UPC	051712147095



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3130 S Dodge Boulevard 85713-0000, AZ Tucson Phone: 520-526-1947 Fax: 520-526-1948

Taxonomies, Classifications, and Cate	egories
Category Description	MIDGET FUSES
Туре	FUSE
Packaging	
Carton	10
Weight Per each	0.02
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems

CE Marked, RoHS Compliant