

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1620 Alcock St. 79065-0000, TX Pampa Phone: 806-665-0433 Fax: 806-665-1002



FP0.500GN48"L Thin-Wall Heat Shrink Tubing, GR, 100PC, 48" Minnesota Mining (3M)

Minnesota Mining (3M) 3M™ Heat Shrink Tubing FP-301 Is A General Purpose, Thin Wall Tubing That Provides A Balance Of Electrical, Physical and Chemical Properties, Making It Ideal For Industrial and Military Applications. This Tubing Has A 2:1 Shrink Ratio and Provides Flame Retardant Insulation For 600V Rated Applications. It Has A Flexible Polyolefin Construction That Offers Moisture Seal Protection. 0.0700 (lbs/each) Splicing & Terminating Kits THIN-WALL HEAT SHRINK TUBING, GR, 100PC, 48" 3M 7000133627 3M™ Heat Shrink Thin- 3M™ Heat Shrink Tubing FP-301 is color coded for quick and easy identification of the wire. This split resistant, flame retardant
Tubing That Provides A Balance Of Electrical, Physical and Chemical Properties, Making It Ideal For Industrial and Military Applications. This Tubing Has A 2:1 Shrink Ratio and Provides Flame Retardant Insulation For 600V Rated Applications. It Has A Flexible Polyolefin Construction That Offers Moisture Seal Protection. 0.0700 (lbs/each) Splicing & Terminating Kits THIN-WALL HEAT SHRINK TUBING, GR, 100PC, 48" 3M 7000133627 3M™ Heat Shrink Thin- 3M™ Heat Shrink Tubing FP-301 is color coded for quick and easy identification of the wire. This split resistant, flame retardant
Splicing & Terminating Kits THIN-WALL HEAT SHRINK TUBING, GR, 100PC, 48" 3M 7000133627 3M™ Heat Shrink Thin- 3M™ Heat Shrink Tubing FP-301 is color coded for quick and easy identification of the wire. This split resistant, flame retardant
Splicing & Terminating Kits THIN-WALL HEAT SHRINK TUBING, GR, 100PC, 48" 3M 7000133627 3M™ Heat Shrink Thin- 3M™ Heat Shrink Tubing FP-301 is color coded for quick and easy identification of the wire. This split resistant, flame retardant
3M 7000133627 3M™ Heat Shrink Thin- 3M™ Heat Shrink Tubing FP-301 is color coded for quick and easy identification of the wire. This split resistant, flame retardant
3M 7000133627 3M™ Heat Shrink Thin- 3M™ Heat Shrink Tubing FP-301 is color coded for quick and easy identification of the wire. This split resistant, flame retardant
3M 7000133627 3M™ Heat Shrink Thin- 3M™ Heat Shrink Tubing FP-301 is color coded for quick and easy identification of the wire. This split resistant, flame retardant
identification of the wire. This split resistant, flame retardant
tubing is used as shrink fit, electrical insulation over cable splices or terminations. The high expansion ratio tubing is mechanically tough, easily markable and resists cold flow. It is ideal for lightweight wire harness covering, fire resistant covering, wire marking, wire bundling and component packaging. It withstands temperatures of 67 to 275 degrees F (55 to 135 degrees
3M™ Heat Shrink Tubing FP-301 is a general purpose, thin wall tubing that provides a balance of electrical, physical and chemical properties, making it ideal for industrial and military applications. This tubing has a 2:1 shrink ratio and provides flame retardant insulation for 600V rated applications. It has a flexible polyolefin construction that offers moisture seal protection.
3M™ Heat Shrink Thin-Wall Flexible Polyolefin Tubing FP-301
3M
00051128599501
FP0.500GN48"L
051128599501



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1620 Alcock St. 79065-0000, TX Pampa Phone: 806-665-0433 Fax: 806-665-1002

Packaging

Carton	800	
Package	100	
Weight Per each	0.07	