



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



FP3013448WH Thin-Wall Heat Shrink Tubing, 3/4 - 48", WH *Minnesota Mining (3M)*

Catalog Number	FP3013448WH
Manufacturer	Minnesota Mining (3M)
Description	3M™ Heat Shrink Tubing FP-301 Is A General Purpose, Thin Wall Tubing That Provides A Balance Of Electrical, Physical and Chemical Properties, Making It Ideal For Industrial and Military Applications. This Tubing Has A 2:1 Shrink Ratio and Provides Flame Retardant Insulation For 600V Rated Applications. It Has A Flexible Polyolefin Construction That Offers Moisture Seal Protection.
Weight per unit	0.1603 (lbs/each)
Product Category	Splicing & Terminating Kits

Descriptions

Description	HEAT SHRINK THIN-WALL TUBING FP-301-3/4-48" WHITE
extra long description	3M 7000133566 3M™ Heat Shrink Thin-
Features	3M™ Heat Shrink Tubing FP-301 is color coded for quick and easy identification of the wire. This split resistant, flame retardant tubing is used as shrink fit, electrical insulation over cable splices or terminations. The high expansion ratio tubing is mechanically tough, easily markable and resists cold flow. It is ideal for lightweight wire harness covering, fire resistant covering, wire marking, wire bundling and component packaging. It withstands temperatures of 67 to 275 degrees F (55 to 135 degrees
Long Description	3M™ Heat Shrink Tubing FP-301 is a general purpose, thin wall tubing that provides a balance of electrical, physical and chemical properties, making it ideal for industrial and military applications. This tubing has a 2:1 shrink ratio and provides flame retardant insulation for 600V rated applications. It has a flexible polyolefin construction that offers moisture seal protection.
Product Type	3M™ Heat Shrink Thin-Wall Flexible Polyolefin Tubing FP-301
Special Features	"Flexible, Polyolefin"

Manufacturer Information

Brand	3M
GTIN	00051128596777
Manufacturers Part Number	FP0.750WT48"H
UPC	051128596777

Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Type	Thin-Wall Flexible Polyolefin



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton 12

Weight Per each 0.1603

Uses, Certifications, and Standards

standard "UL, CSA, ABS"