



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



FP3013848 Thin-Wall Heat Shrink Tubing, 3/8 - 48" , BK *Minnesota Mining (3M)*

| | |
|------------------|---|
| Catalog Number | FP3013848 |
| Manufacturer | Minnesota Mining (3M) |
| Description | 3M™ Heat Shrink Tubing FP-301 Is A General Purpose, Thin Wall Tubing That Provides A Balance Of Electrical, Physical and Chemical Properties, Making It Ideal For Industrial and Military Applications. This Tubing Has A 2:1 Shrink Ratio and Provides Flame Retardant Insulation For 600V Rated Applications. It Has A Flexible Polyolefin Construction That Offers Moisture Seal Protection. |
| Weight per unit | 0.1200 (lbs/each) |
| Product Category | Splicing & Terminating Kits |

Descriptions

| | |
|------------------------|--|
| Description | HEAT SHRINK THIN-WALL TUBING 3/8-48"-BLACK-12PC |
| extra long description | 3M 7100007365 3M™ Heat Shrink Thin- |
| Features | 3M™ Heat Shrink Tubing FP-301 is color coded for quick and easy identification of the wire. This split resistant, flame retardant tubing is used as shrink fit, electrical insulation over cable splices or terminations. The high expansion ratio tubing is mechanically tough, easily markable and resists cold flow. It is ideal for lightweight wire harness covering, fire resistant covering, wire marking, wire bundling and component packaging. It withstands temperatures of 67 to 275 degrees F (55 to 135 degrees |
| Long Description | 3M™ Heat Shrink Tubing FP-301 is a general purpose, thin wall tubing that provides a balance of electrical, physical and chemical properties, making it ideal for industrial and military applications. This tubing has a 2:1 shrink ratio and provides flame retardant insulation for 600V rated applications. It has a flexible polyolefin construction that offers moisture seal protection. |
| Product Type | 3M™ Heat Shrink Thin-Wall Flexible Polyolefin Tubing FP-301 |
| Special Features | Flexible, Polyolefin |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | 3M |
| GTIN | 00051128595848 |
| Manufacturers Part Number | 7100007365 |
| UPC | 051128595848 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|--------------------|
| Category Description | HEAT/COLD SHRINK |
| Type | Single (Thin) Wall |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton 12

Weight Per each 0.12

Uses, Certifications, and Standards

standard UL, CSA, ABS