

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### FRNR712 7-1/2A 250V TD Class RK5 Dual Elem Fuse-Fusetron Bussmann Fuses

	EDUDA40	
Catalog Number	FRNR712	
Manufacturer		
Description	Eaton Bussmann Series FRN-R Fuse, 7.5 A, Dual, Class RK5, Non-Indicating, Ferrule End X Ferrule End, 8 Sec At 500%, 200 Kaic At 250 V, 20 Kaic At 125 VDC, Standard, 250 V, 125 VDC	
Weight per unit	0.0600 (lbs/each)	
Product Category		
Features		
amperage rating	7.5 A	
class	Class RK5	
connection	Ferrule End X Ferrule End	
dimensions	0.5600 IN X 0.5600 IN X 2.0000 IN	
element	Dual	
interrupt rating	20 kAIC at 125 Vdc200 kAIC at 250 Vac	
media	Yes	
Response Time	8 S at 500%	
Voltage Rating	250 VAC, 125 VDC	
Dimensions and Weight		
Size	0.56 In Diameter X 2.00 In Length	
Descriptions		
Description	7-1/2A 250V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON	
extra long description		
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of time-delay at 500% of rated current (8 seconds for 1/10-30A sizes).	
Long Description	Eaton Bussmann series FRN-R fuse, 7.5 A, Dual, Class RK5, Non-indicating, Ferrule end x ferrule end, 8 sec at 500%, 200 kAlC at 250 V,20 kAlC at 125 Vdc, Standard, 250 V, 125 Vdc	
Product Type	Fusetron Dual-Element Class RK5	
<b>J</b> .		



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	Inform	

Brand	COOPER BUSSMANN
GTIN	00051712506977
Manufacturers Part Number	FRN-R-7-1/2
UPC	051712506977

#### **Taxonomies, Classifications, and Categories**

Category Description	Fuses & Fuse Accessories
Tyne	FUSF

#### **Packaging**

gg	
Carton	10
Weight Per each	0.06

#### Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked