

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



-	COL	-	1
Ħ	-		
	-		×

Catalog Number	FS12
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet FS Device Box, Shallow, Feraloy Iron Alloy, Two-Gang, 1/2"
Weight per unit	3.2 (lbs/each)
Product Category	FS & FD Type Boxes & Covers

Features

Cable Entry	(1) End
dimensions	4.6300 IN X 1.8800 IN X 5.1900 IN
Material	Electrogalvanized With Aluminum Acrylic Painted Feraloy Iron
	Alloy

Dimensions and Weight

Size 1/2 in

Descriptions

Description	2G FS-DEV BOX, 1/2"
extra long description	CRS-H FS12 1/2 NPT CST IRON FS BX T
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hub configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Long Description	Eaton Crouse-Hinds series Condulet FS device box, Shallow, Feraloy iron alloy, Two-gang, 1/2"
Product Type	1/2 NPT CST Iron FS BX Two GNG MTG Lugs
Special Features	Configuration Type FS, With Mounting Lug, Dimension 4-5/8 In Width X 1-7/8 In Depth X 5-3/16 In Height

Manufacturer Information

Brand	Eaton
GTIN	00782274406404
Manufacturers Part Number	FS12
UPC	782274406404



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	gories
Category Description	FS BOXES AND COVERS
Туре	DEVICE BOX
Packaging	
Carton	1
Weight Per each	3.15
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	SURFACE

UL 514, CSA C22.2, Federal Specification W-C-5860