

FIBERGLASS

STEPLADDER FS1500 SERIES

300 lbs. **TYPE IA**
load capacity*



- ☐ Da Boot™ Patent #7,000,731 B2
- ☐ Molded Top with Tool Slots
- ☐ Inside spreader braces
- ☐ Double-rivet step construction
- ☐ Wide Back Braces
- ☐ Full channel fiberglass rail



ANSI
Meets or exceeds requirements
of American National Standards Institute
ANSI A14.5



MODEL	SIZE	STEP SIZE	BOTTOM WIDTH	APPROX. SPREAD	APPROX. WT. (LBS)	APPROX. CUBES
FS1502*	2'	3"	17"	18 1/4"	8	2.07'
FS1503	3'	3"	18 7/8"	28"	12	3.18'
FS1504	4'	3"	199/16"	2815/16"	14	3.18'
FS1505	5'	3"	211/16"	34 7/8"	17	4.27'
FS1506	6'	3"	229/16"	40 7/8"	20	5.49'
FS1508	8'	3"	259/16"	52 3/4"	26	8.29'
FS1510	10'	3"	289/16"	6411/16"	34	11.67'
FS1512	12'	3"	319/16"	76 1/16"	47	15.49'

*FS1502 is a folding step stand and is not equipped with Da Boot™

FIBERGLASS

STEPLADDER FS2000 SERIES

250 lbs. **TYPE I**
load capacity*

- ☐ Slip resistant rubber feet
- ☐ Molded Top with Handyman's Tool Slots
- ☐ Pinch resistant spreader braces
- ☐ Double-rivet step construction
- ☐ Optional Molded Pail Shelf



ANSI
Meets or exceeds requirements
of American National Standards Institute
ANSI A14.5



MODEL	SIZE	STEP SIZE	BOTTOM WIDTH	APPROX. SPREAD	APPROX. WT. (LBS)	APPROX. CUBES
FS2004	4'	3"	18 13/16"	28 3/16"	12	3.18'
FS2005	5'	3"	20 5/16"	34 1/8"	15	4.27'
FS2006	6'	3"	21 13/16"	40"	17	5.49'
FS2008	8'	3"	24 13/16"	51 7/8"	22	8.29'

FIBERGLASS

STEPLADDER FS4000 SERIES

225 lbs. **TYPE II**
load capacity*

- ☐ Molded Top with Tool Slots
- ☐ Slip resistant Feet
- ☐ Pinch resistant spreader braces
- ☐ Fiberglass rails



ANSI
Meets or exceeds requirements
of American National Standards Institute
ANSI A14.5



MODEL	SIZE	BASE WIDTH	SPREAD	APPROX. WT. (LBS)	APPROX. CUBES
FS4004	4'	18 3/16"	28 3/16"	11	2.7'
FS4006	6'	21 13/16"	40 1/16"	16	4.4'
FS4007	7'	23 5/16"	46"	18	5.3'
FS4008	8'	24 13/16"	51 7/8"	21	6.2'

FIBERGLASS

STEPLADDER FS1500 SERIES

300 lbs. **TYPE IA**
load capacity*



- ☐ Da Boot™ Patent #7,000,731 B2
- ☐ Molded Top with Tool Slots
- ☐ Inside spreader braces
- ☐ Double-rivet step construction
- ☐ Wide Back Braces
- ☐ Full channel fiberglass rail



ANSI
Meets or exceeds requirements
of American National Standards Institute
ANSI A14.5



MODEL	SIZE	STEP SIZE	BOTTOM WIDTH	APPROX. SPREAD	APPROX. WT. (LBS)	APPROX. CUBES
FS1502*	2'	3"	17"	18 1/4"	8	2.07'
FS1503	3'	3"	18 7/8"	28"	12	3.18'
FS1504	4'	3"	199/16"	2815/16"	14	3.18'
FS1505	5'	3"	211/16"	34 7/8"	17	4.27'
FS1506	6'	3"	229/16"	40 7/8"	20	5.49'
FS1508	8'	3"	259/16"	52 3/4"	26	8.29'
FS1510	10'	3"	289/16"	6411/16"	34	11.67'
FS1512	12'	3"	319/16"	76 1/16"	47	15.49'

*FS1502 is a folding step stand and is not equipped with Da Boot™

FIBERGLASS

STEPLADDER FS2000 SERIES

250 lbs. **TYPE I**
load capacity*

- ☐ Slip resistant rubber feet
- ☐ Molded Top with Handyman's Tool Slots
- ☐ Pinch resistant spreader braces
- ☐ Double-rivet step construction
- ☐ Optional Molded Pail Shelf



ANSI
Meets or exceeds requirements
of American National Standards Institute
ANSI A14.5



MODEL	SIZE	STEP SIZE	BOTTOM WIDTH	APPROX. SPREAD	APPROX. WT. (LBS)	APPROX. CUBES
FS2004	4'	3"	18 13/16"	28 3/16"	12	3.18'
FS2005	5'	3"	20 5/16"	34 1/8"	15	4.27'
FS2006	6'	3"	21 13/16"	40"	17	5.49'
FS2008	8'	3"	24 13/16"	51 7/8"	22	8.29'

FIBERGLASS

STEPLADDER FS4000 SERIES

225 lbs. **TYPE II**
load capacity*

- ☐ Molded Top with Tool Slots
- ☐ Slip resistant Feet
- ☐ Pinch resistant spreader braces
- ☐ Fiberglass rails



ANSI
Meets or exceeds requirements
of American National Standards Institute
ANSI A14.5



MODEL	SIZE	BASE WIDTH	SPREAD	APPROX. WT. (LBS)	APPROX. CUBES
FS4004	4'	18 3/16"	2813/16"	11	2.7'
FS4006	6'	21 13/16"	401/16"	16	4.4'
FS4007	7'	23 5/16"	46"	18	5.3'
FS4008	8'	24 13/16"	51 7/8"	21	6.2'