


## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





## FST250KIT 8.5-Oz Foam Duct Sealant Kit Bulk 6PK

American Polywater

Catalog Number	FST250KIT
Manufacturer	American Polywater
Description	Same As Kit Above In A Box Of 6. Protects Conduit and Raceway Systemsfst™ Closed-Cell Sealant Provides Superior Pressure-Blocking In The Toughest Environments. It Stops Water Methane, and Other Gases to Keep Electrical Systems Intact. FST Duct Sealant Is Durable and Easy to Install. FST Is Chemically Resistant and Has Excellent Adhesion to Conduits.
Weight per unit	1.8 (lbs/each)
Product Category	Paint, Chemicals, Etc.
Features	
specific gravity	1.22 @25° C
Temperature Range	-20°F - 200°F
Material, Color, and Finish	
Color	Brown liquid, tan foam
<b>Dimensions and Weight</b>	
Size	8.5
Descriptions	
Description	8.5-OZ FOAM DUCT SEALANT KIT BULK 6PK
extra long description	PWTR FST-250KIT 8.5-Oz Foam Duct Se
Long Description	Same as kit above in a box of 6. Protects Conduit and Raceway
	SystemsFST™ closed-cell sealant provides superior
	pressure-blocking in the toughest environments. It stops water, methane, and other gases to keep electrical systems intact. FST Duct Sealant is durable and easy to install. FST is chemically resistant and has excellent adhesion to conduits.
Product Type	8.5-Oz Foam Duct Sealant Kit Bulk 6-Pack
Special Features	duct sealant, reenterable, closed cell, water block, durable, easy install,
Manufacturer Information	
Brand	AMERICAN POLYWATER
GTIN	00027868045714
Manufacturers Part Number	FST-250KIT
sub brand	FST, Foam Duct Sealant
UPC	027868045714



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

stnadard 5.1.1.2.8,5.4.2.3, 7.4.2.8.1; UL 94, IEEE1210,

Taxonomies, Classifications, ar	nd Categories
Category Description	ADHESIVES
Туре	Foam Duct Sealant
Packaging	
Carton	6
Weight Per each	1.8333
Uses, Certifications, and Stand	ards
Application	closed-cell duct sealant prviding superior pressure-blocking power
standard	NEC Article 225.27, 230.8, 300.5, 300.7, 501.15; TIA-758-B