

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

G4X4LG6 SLTD	Wiring Duct
Developit Commence the	

Panduit Corporation

Catalog Number	G4X4LG6
Manufacturer	Panduit Corporation
Description	The G4X4LG6 Panduct Lead-Free PVC Wide Slot Wiring Duct
	Feature A Wide Slot/Finger Design That Provides Greater
	Sidewall Rigidity and Is Suitable With A Range Of Wire Bundle
	Sizes. UI 94 Flame Class Of V-0 With A UI Recognized
	Continuous-Use Temperature Up to 122°F (50°C). Mounting
	Holes Provided. 4.0" X 4.0" (101.6 MM X 101.6 MM) and 6' (1.8
	M) Long. Cover Sold Separately. Color Light Gray.
Weight per unit	
Product Category	Ducts, Raceways, Runways, Tray
Features	
connection	Mounting Holes
Material	PVC
media	Yes
Material, Color, and Finish	
Color	Light Gray
Dimensions and Weight	
Length	NA
Size	4.25 x 4.10
Width	4.25
Descriptions	
Description	SLTD WIRING DUCT
extra long description	PAN G4X4LG6 Panduct [®] G4X4LG6 Base W
Long Description	The G4X4LG6 Panduct Lead-Free PVC Wide Slot Wiring Duct
	feature a wide slot/finger design that provides greater sidewall
	rigidity and is suitable with a range of wire bundle sizes. UL 94
	flame class of V-0 with a UL recognized continuous-use
	temperature up to 122°F (50°C). Mounting holes provided. 4.0" x
	4.0" (101.6 mm x 101.6 mm) and 6' (1.8 m) long. Cover sold
	separately. Color Light Gray.
Product Type	Panduct [®] G4X4LG6 Base Wiring Duct
Manufacturer Information	
Brand	PANDUIT
GTIN	00074983545933
Manufacturers Part Number	G4X4LG6
UPC	074983545933



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	WIRE DUCT AND COVERS		
Туре	Base Wiring Duct		
Packaging			
Carton	60		
Weight Per each	0.0662		
Uses, Certifications, and Standards			
Application	Wide slot/finger design provides greater sidewall rigidity and can be used in a wide range of applications		
standard	RoHS Compliant, UL Recognized, CE Compliant; CSA Approved		