

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



GFTCB240 BR 2 Pole 40A GFST 120/240V 10 Kaic #14-4 Awg *Eaton Corp*

Catalog Number	GFTCB240
Manufacturer	Eaton Corp
Description	Eaton BR Gfci Circuit Breaker, Ground Fault Personnel Protection Circuit Breakers, 40 A, 10 Kaic, Two-Pole, 120/240 V, GFTCB, Common, #14-4 Awg, Ground Fault Circuit Interrupter, GFI
Weight per unit	0.8000 (lbs/each)
Product Category	In Circuit Breakers
Features	
dimensions	4.5000 IN X 2.7500 IN X 2.0000 IN
interrupt rating	10
Poles	2
Voltage Rating	120/240 V
Descriptions	
Description	BR 2 POLE 40A GFST 120/240V 10 KAIC #14-4 AWG
extra long description	ETN GFTCB240 BR 2 POLE 40A GFST, 12
Features	Eaton's BR circuit breakers are used in indoor and outdoor BR loadcenters, spa panels, meter breakers and sub panels. They are designed for a wide range of applications such as high short-circuit interrupt, series rating combinations with upstream main breakers, thermal magnetic, AFCI, GFCI, equipment protection and dual function AF/GF.
Long Description	Eaton BR GFCI circuit breaker, Ground fault personnel protection circuit breakers, 40 A, 10 kAIC, Two-pole, 120/240 V, GFTCB, Common, #14-4 AWG, Ground fault circuit interrupter, GFI
Product Type	BR 2 Pole 40A GFST, 120/240V, 10 Kaic
Manufacturer Information	
Brand	Eaton
GTIN	00786676025973
Manufacturers Part Number	GFTCB240
UPC	786676025973
Taxonomies, Classifications, and	Categories
Category Description	Fault Sensing Breakers (AFCI/GFCI)
Туре	GFCI circuit breakers
Packaging	
Carton	1
Weight Per each	0.8

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

es, cei illications, and sta	i iudi us
Application	Generation - Renewable Energy - Alternative EnergyGeneration -
	Conventional Energy - Conventional EnergyMarine Vessels and
	Equipment - Marine Vessels and Equipment - OtherDatacenters -
	IT Space: CI and Hyper ConvergedOther
standard	UL 489,UL 943