

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Package

Weight Per each

GX2929 2/0-250 Cop Ground Conn Burndy LLC

Catalog Number	GX2929
Manufacturer	Burndy LLC
Description	Mechanical Grounding Connector, Cable Cross Connection, 2/0 Awg (Sol.) - 250 Kcmil (Run), 2/0 Awg (Sol.) - 250 Kcmil (Tap), 3/8" Stud.
Weight per unit	0.6200 (lbs/each)
Product Category	Large Terminals & Connectors
eatures	
Material	COPPER ALLOY
Descriptions	
Description	2/0-250 COP GROUND CONN
extra long description	BUR GX2929 2/0-250 TO 2/0-250 X CON
Long Description	Mechanical Grounding Connector, Cable Cross Connection, 2/0 AWG (Sol.) - 250 kcmil (Run), 2/0 AWG (Sol.) - 250 kcmil (Tap), 3/8" Stud.
Product Type	Mechanical
Special Features	Features: High Copper Alloy Ground Connector For Cross Connecting A Wide Range Of Cable, The High Copper Alloy Cast Body, DURIUM U-Bolts, Nuts, And Lockwashers Make The GX Suitable For Burial In Soil Or Concrete, One-Wrench Installation, UL467 Listed, Acceptable For Direct Burial In Earth Or Concrete, Installation Torque: 240 IN-LB, Length: 1-7/8 IN, Height: 2-3/4 IN Width: 1-7/8 IN
/lanufacturer Information	
Brand	BURNDY
GTIN	00781810260692
Manufacturers Part Number	GX2929
UPC	781810260692
axonomies, Classifications, and (Categories
Category Description	SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding Fittings & Ground Rods
Туре	GX
Packaging	
Carton	1

50

0.62

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	For Cross Connecting A Wide Range Of Copper Cable, Direct
	Burial In Earth Or Concrete
standard	UL467