



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## H050 STR Male L/T Conn, 1/2", Steel

*Hubbell Wiring Devices*

|                  |   |
|------------------|---|
| Catalog Number   | H050  |
| Manufacturer     | Hubbell Wiring Devices  |
| Description      | Kellems Wire Management, Liquidtight System, Straight Male Liquid Tight Connector, 1/2", Steel, Non-Insulated |
| Weight per unit  | 0.1500 (lbs/each)   |
| Product Category | Liquid Tight Fittings   |

### Features

|                 |                    |
|-----------------|--------------------|
| connection      | Cap Nut            |
| Material        | Steel, Zinc Plated |
| pallet quantity | 12000              |

### Material, Color, and Finish

|        |          |
|--------|----------|
| Color  | Metallic |
| Finish | Metallic |

### Dimensions and Weight

|        |        |
|--------|--------|
| Length | 1.437  |
| Size   | 1/2 in |
| Width  | 1.188  |

### Descriptions

|                        |   |
|------------------------|---|
| Description            | STR MALE L/T CONN, 1/2", STEEL  |
| extra long description | HWDK H050 STR MALE L/T CONN, 1/2",  |
| Features               | Insulated and Non-Insulated Conduit Connectors - Hubbell offers a broad line of metallic liquidtight fittings for use with metallic liq-uidtight conduits and Polytuff I. Hubbell offers trade sizes from 3/8" to 4" in straight,45°, and 90° body designs. Most connectors are available with either insulated ornon-insulated throats. Liquidtight fittings are precision manufactured to exactingstandards assuring ease of use and reliability. Straight body 1/2" and 3/4" sizes are list-ed for UL Type 3R, 4, 12 and 13 envi |
| Long Description       | Kellems Wire Management, Liquidtight System, Straight Male Liquid Tight Connector, 1/2", Steel, Non-Insulated   |
| Product Type           | Metallic Liquidtight Fittings   |
| Special Features       | Non-Insulated   |

### Manufacturer Information

|                           |                       |
|---------------------------|-----------------------|
| Brand                     | WIRING DEVICE-KELLEMS |
| GTIN                      | 00783585034027        |
| Manufacturers Part Number | H050                  |
| UPC                       | 783585034027          |



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

|                      |                               |
|----------------------|-------------------------------|
| Category Description | Stainless Steel EMT Conduit   |
| Type                 | Metallic Liquidtight Fittings |

## Packaging

|                 |      |
|-----------------|------|
| Carton          | 1    |
| Package         | 50   |
| Weight Per each | 0.15 |

## Uses, Certifications, and Standards

|                          |   |
|--------------------------|---|
| Application              | For use with Liquidtight Metal conduit and PolyTuff I<br>Non-Metallic conduit                   |
| environmental conditions | Suitable for use in wet locations when a listed sealing ring is used<br>between box and fitting |
| Mounting                 | Between Enclosure and Conduit   |
| nema rating              | Suitable for use in hazardous locations per Class 1 Div 2                                       |
| standard                 | CSA Certified;UL 514B   |