



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



H050 STR Male L/T Conn, 1/2" , Steel

Hubbell Wiring Devices

| | |
|------------------|--|
| Catalog Number | H050 |
| Manufacturer | Hubbell Wiring Devices |
| Description | Kellems Wire Management, Liquidtight System, Straight Male Liquid Tight Connector, 1/2" , Steel, Non-Insulated |
| Weight per unit | 0.1500 (lbs/each) |
| Product Category | Liquid Tight Fittings |

Features

| | |
|-----------------|--------------------|
| connection | Cap Nut |
| Material | Steel, Zinc Plated |
| pallet quantity | 12000 |

Material, Color, and Finish

| | |
|--------|----------|
| Color | Metallic |
| Finish | Metallic |

Dimensions and Weight

| | |
|--------|--------|
| Length | 1.437 |
| Size | 1/2 in |
| Width | 1.188 |

Descriptions

| | |
|------------------------|---|
| Description | STR MALE L/T CONN, 1/2", STEEL |
| extra long description | HWDK H050 STR MALE L/T CONN, 1/2" |
| Features | Insulated and Non-Insulated Conduit Connectors - Hubbell offers a broad line of metallic liquidtight fittings for use with metallic liq-uidtight conduits and Polytuff I. Hubbell offers trade sizes from 3/8" to 4" in straight,45°, and 90° body designs. Most connectors are available with either insulated ornon-insulated throats. Liquidtight fittings are precision manufactured to exactingstandards assuring ease of use and reliability. Straight body 1/2" and 3/4" sizes are list-ed for UL Type 3R, 4, 12 and 13 envi |
| Long Description | Kellems Wire Management, Liquidtight System, Straight Male Liquid Tight Connector, 1/2" , Steel, Non-Insulated |
| Product Type | Metallic Liquidtight Fittings |
| Special Features | Non-Insulated |

Manufacturer Information

| | |
|---------------------------|-----------------------|
| Brand | WIRING DEVICE-KELLEMS |
| GTIN | 00783585034027 |
| Manufacturers Part Number | H050 |
| UPC | 783585034027 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

| | |
|----------------------|-------------------------------|
| Category Description | Stainless Steel EMT Conduit |
| Type | Metallic Liquidtight Fittings |

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Package | 50 |
| Weight Per each | 0.15 |

Uses, Certifications, and Standards

| | |
|--------------------------|---|
| Application | For use with Liquidtight Metal conduit and PolyTuff I Non-Metallic conduit |
| environmental conditions | Suitable for use in wet locations when a listed sealing ring is used between box and fitting |
| Mounting | Between Enclosure and Conduit |
| nema rating | Suitable for use in hazardous locations per Class 1 Div 2 |
| standard | CSA Certified;UL 514B |