

## **ELLIOTT ELECTRIC SUPPLY**

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## HBL2723ST LKG Conn, 30A 3P 250V, L15-30R, SPT Hubbell Wiring Devices

Catalog Number	HBL2723ST
Manufacturer	Hubbell Wiring Devices
Description	Locking Devices, Edgeconnect™ Twist-Lock®, Industrial, Female
	Connector Body, 30A 3-Phase Delta 250V Ac, 3-Pole 4-Wire
	Grounding, L15-30R, Screwless Terminal, Black and White
Weight per unit	0.4500 (lbs/each)
Product Category	Wiring Devices
eatures	
connection	EdgeConnect <sup>™</sup> Screwless Termination
Material	Nylon
Poles	3
Voltage Rating	3P 250
Naterial, Color, and Finish	
Color	Black;White
imensions and Weight	
Size	Standard Sized Product
escriptions	
Description	LKG CONN, 30A 3P 250V, L15-30R, SPT
extra long description	HWDK HBL2723ST LKG CONN, 30A 3P 250
Features	EdgeConnect <sup>™</sup> Screwless Termination system, simply insert the
	wire and press the plunger down. No tools are required. That
	connection is fool-proof and long lasting, to all but guarantee a
	high quality result. Any qualified installer regardless of level of
	training can guarantee a high quality result.
Long Description	Locking Devices, EdgeConnect™ Twist-Lock <sup>®</sup> , Industrial, Female
	Connector Body, 30A 3-Phase Delta 250V AC, 3-Pole 4-Wire
	Grounding, L15-30R, Screwless Terminal, Black and White
Product Type	LKG Conn, 30A 3P 250V, L15-30R, SP T
Special Features	EdgeConnect <sup>™</sup> Technology, Screwless Termination
Nanufacturer Information	
Brand	WIRING DEVICE-KELLEMS
GTIN	00783585719108
Manufacturers Part Number	HBL2723ST
series	EdgeConnect™
UPC	783585719108



## $E_{\text{LLIOTT}} E_{\text{LECTRIC}} S_{\text{UPPLY}}$

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description	NEMA RATED TURNLOK PLUGS, CONNECTORS, & RECEPTICLES
Туре	CONNECTOR
Packaging	
Carton	1
Package	30
Weight Per each	0.45
Uses, Certifications, and Standards	
environmental conditions	IP20 Suitability
Mounting	SCREW
nema rating	L15-30R
standard	Listed to UL 498, Fed.Spec. W-C-596, Certified to CSA C22.2 No.42