



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



HBL320P7W PS, IEC, Plug, 2P3W, 20A 480V, 4X/69K *Hubbell Wiring Devices*

Catalog Number	HBL320P7W
Manufacturer	Hubbell Wiring Devices
Description	Heavy Duty IEC Pin and Sleeve Industrial Grade Male Plug 20A 480V Ac, 2-Pole 3-Wire Grounding, Terminal Screws, Watertight
Weight per unit	0.8500 (lbs/each)
Product Category	Pin & Sleeve Devices

Features

amperage rating	20
connection	Screwed Terminal
Cord Type	All Portable
Current Rating	20
Material	COMPOSITE
Number of Wires	3-Wire
Phase	1
Poles	2-Pole
Voltage Rating	480
Wire Size	#14 to #10

Dimensions and Weight

Size	Standard Sized
------	----------------

Descriptions

Description	PS, IEC, PLUG, 2P3W, 20A 480V,4X/69K
extra long description	HWDK HBL320P7W PS, IEC, PLUG, 2P3W,
Features	Watertight Devices - Hubbell's IEC 60309 Pin and Sleeve plugs, connectors, inlets and receptacles are the highest performing products available. The HBL® series of IEC pin and sleeve were designed for the demanding North American market. Hubbell was the first and is still only manufacturer of IEC 60309 devices in the USA and have numerous innovative features noted below. The IEC line of plugs and connectors are made with a rugged super tough, one-piece housing. The thermoset polyester contact carrier provi
Long Description	Heavy Duty IEC Pin and Sleeve Industrial Grade Male Plug 20A 480V AC, 2-Pole 3-Wire Grounding, Terminal Screws, Watertight
Product Type	PS, IEC, Plug, 2P3W, 20A 480V, 4X/69K
Special Features	Watertight



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585403410
Manufacturers Part Number	HBL320P7W
series	HBL Heavy Duty
UPC	783585403410

Taxonomies, Classifications, and Categories

Category Description	Pin & Sleeve Devices
Type	Watertight Plug

Packaging

Carton	1
Package	10
Weight Per each	0.85

Uses, Certifications, and Standards

Application	High Ampacity Connections
environmental conditions	Watertight
Mounting	Cord
nema rating	Non-NEMA
standard	CSA Certified File LR280C;UL Classified to IEC 60309-1 IEC 60309-2;UL Standard UL1682 and UL 1686C2