

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



HBL8200RED Dup RCPT, HG, 15A 125V, 5-15R, RD Hubbell Wiring Devices

Catalog Number	HBL8200RED
Manufacturer	Hubbell Wiring Devices
Description	Straight Blade Devices, Receptacles, Duplex, Hospital Grade, 2-POLE3-Wire Grounding, 15A 125V, 5-15R, Red.
Weight per unit	0.2500 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro

Features

itaros	
amperage rating	15
connection	Screw Terminals
Current Rating	15
Dielectric Strength	Withstands 2,000V minimum
Material	Nylon
Number of Wires	3-Wire
pallet quantity	4500
Phase	1
Poles	2-Pole
Voltage Rating	125 V
Wattage	1875
Wire Size	#14 to #10

Dimensions and Weight

Descriptions

Description	DUP RCPT, HG, 15A 125V, 5-15R, RD
extra long description	HWDK HBL8200RED DUP RCPT, HG, 15A 1
Features	HBL® Extra Heavy Duty Max Hospital Grade Devices - UL requirements for Hospital Grade devices is more stringent than those for standard devices. Hubbell receptacles are designed to meet and exceed the standards with Exclusive nickel-plated bypass contact design increases contact pressure, lowering the operating temperature; Four point grounding system provides redundant grounding for low resistance ground continuity in high abuse areas; Impact resistant deep face design prevents breakage. Because of these
Long Description	Straight Blade Devices, Receptacles, Duplex, Hospital Grade, 2-Pole3-Wire Grounding, 15A 125V, 5-15R, Red.
Product Type	Dup RCPT, HG, 15A 125V, 5-15R, RD
Special Features	Standard Product



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Ν	Л	an	uf	act	tur	er	Inf	orr	ma	tior	1
---	---	----	----	-----	-----	----	-----	-----	----	------	---

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585247526
Manufacturers Part Number	HBL8200RED
series	Hospital Grade
UPC	783585247526

Taxonomies, Classifications, and Categories

Category Description	Industrial receptacles
Туре	RECEPTACLE

Packaging

Carton	1	
Package	10	
Weight Per each	0.25	

Uses, Certifications, and Standards

Application	Hospital grade
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Screw Mount
nema rating	5-15R
standard	CSA Certified, C22.2, No. 42 File 285; Fed. Spec. W-C-596; NEMA®
	WD-6 Compliant; UL Listed to UL498 File No. E2186