

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



HBL8300RED Dup RCPT, HG, 20A 125V, 5-20R, RD Hubbell Wiring Devices

QaQ	
Catalog Number	HBL8300RED
Manufacturer	Hubbell Wiring Devices
Description	Straight Blade Devices, Receptacles, Duplex, Hospital Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5-20R, Red, Single Pack.
Weight per unit	0.0780 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro
eatures	
amperage rating	20
connection	Dock and Sida Wirod Sarow Terminals
Current Rating	20
Dielectric Strength	Withstands 2,000V minimum
Number of Wires	3-Wire
pallet quantity	3600
Phase	1
Poles	2-Pole
Voltage Rating	
Wattage	2500
Wire Size	#10 to #10
imensions and Weight	
Size	3.28 in x 1.65 in x 1.19 in
escriptions	
Description	DUP RCPT, HG, 20A 125V, 5-20R, RD
extra long description	HWDK HBL8300RED DUP RCPT, HG, 20A 1
Features	HBL® Extra Heavy Duty Max Hospital Grade Devices - UL requirements for Hospital Grade devices is more stringent than those for standard devices. Hubbell receptacles are designed to meet and exceed the standards with Exclusive nickel-plated bypass contact design increases contact pressure, lowering the operating temperature; Four point grounding system provides redundant grounding for low resistance ground continuity in hig abuse areas; Impact resistant deep face design prevents breakage. Because of these
	-
Long Description	Straight Blade Devices, Receptacles, Duplex, Hospital Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5-20R, Red, Single Pack.
Long Description Product Type Special Features	



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585247533
Manufacturers Part Number	HBL8300RED
series	Hospital Grade
UPC	783585247533
Taxonomies, Classifications, and Cate	egories
Category Description	Industrial receptacles
Туре	RECEPTACLE
Packaging	
Carton	1
Package	10
Weight Per each	0.078
Uses, Certifications, and Standards	
Application	Hospital grade
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Screw Mount
nema rating	5-20R
standard	CSA Certified, C22.2, No. 42 File 285;Fed. Spec. W-C-596;NEMA® WD-6 Compliant;UL Listed to UL498 File No. E2186